





Powered by Slide Li-ion Battery of Makita's New 10.8V Platform



Two switch levers are available with variable speed control.

Multi-position switch to make operation easier at any grip position for versatile applications by pulling either trigger.











JR103D

Toolless blade clamp for Recipro saw blade





JR105D

Blade clamp compatible with both Recipro and Jig saw blades



▲ On-tool storage for hex wrench



LED job light



Li-ion Battery & Charger Time Reference, Compatibility Chart



Performance Comparison

Note: 1. The test results depend to a great extent on the hardness of materials, etc.

2. The numbers in the bar graphs are relative values when the capacity of **Competitor "M"** is indexed at 100.

Vork speed ← sl	ow	fast →		
Makita JR103/ JR1	05D			150
Competitor "D"			127	
Competitor "M"		100		
) 5	0	1(00	15

Battery fuel gauge

(BL1020B, BL1040B)

The power remaining in the battery can be indicated in 4 stages simply by pushing a button.



Battery fuel gauge (4 stage LED)

Forced air cooling system

DC10SA only

•Stand-by time until the charge starts can be greatly shortened by using charger DC10SA equipped with a

built-in cooling fan.
•Effectively cools
down every battery
cell with the forced
air cooling system
and the heat sinks.



JR103D/JR105D Capacity **Pipe:** 50mm (2") Wariable Speed Wood: 50mm (2") Length of stroke 13mm (1/2") Brake Strokes per minute (spm) Dimensions 0-3.300 376x66x186mm Bayonet Shank Jig Saw Blade (JR105D only) (14-3/4"x2-5/8"x7-3/8") BL1015: 1.3kg (2.9lbs) (LxWxH) Built-in Job Light Net weight BL1040B: 1.5kg (3.3lbs)

Standard Equipment:

Recipro saw blades

*weiaht accordina to EPTA-Procedure 01/2003

Carrying Case

Items of standard equipment and specifications may vary by country or area.

Makita Corporation

Battery, Charger, Battery cover, Hex wrench,

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan