

## AC 2,200W high performance portable cut-off

**M2403**

Vertical handle



### Cutting Capacity


Cross section of workpiece	Cutting angle	90°	45°
			ø127mm (5")
 D: Diameter W: Width H: Height		H x W: 102 x 194mm (4" x 7-5/8")	H x W: 115 x 103mm (4-1/2" x 4-1/16")
		H x W: 70 x 233mm (2-3/4" x 9-1/8")	
 S: Side T: Thickness		H x W: 119 x 119mm (4-11/16" x 4-11/16")	H x W: 106 x 106 (4-3/16" x 4-3/16")
		S x S: 137 x 137mm, T: 10mm (5-3/8" x 5-3/8", 3/8")	S x S: 100 x 100mm, T: 10mm (4" x 4", 3/8")

Horizontal handle (for M2402 only)



Adjustable guide plate with 3 settings provides three angle settings up to 45 degrees left and right with stops at 15 and 30 degrees.

Quick release vise



**M2402**



### Portable Cut-off

**M2402 / M2403 355 mm (14")**

203

Double Insulation

<b>Continuous rating input</b>	2,200W
<b>Wheel Diameter</b>	355 mm (14")
<b>Wheel Arbor</b>	25.4 mm (1")
<b>Wheel Thickness</b>	3 mm (1/8")
<b>No Load Speed (RPM)</b>	3,800
<b>Vibration Level</b>	M2402: 4.5 m/s <sup>2</sup> M2403: 3.5 m/s <sup>2</sup>
<b>Sound Pressure Level</b>	M2402: 98 dB(A) M2403: 99 dB(A)
<b>Sound Power Level</b>	M2402: 108 dB(A) M2403: 109 dB(A)
<b>Dimensions (L x W x H)</b>	M2402: 490x280x610mm (19-1/4"x11"x24") M2403: 500x280x620mm (19-3/4"x11"x24-3/8")
<b>Net weight</b>	M2402: 14.5 kg (32.0 lbs) M2403: 14.3 kg (31.5 lbs)
<b>Power supply cord</b>	2.0 m (6.6 ft)

**Standard Equipment :**  
Abrasive Cut-Off Wheel, Hex Wrench

Weight according to EPTA-Procedure 01/2014

Items of standard equipment and specifications may vary by country or area.

## Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202010