



Satisfy Professional's Needs



Cordless Impact Wrench

18V
LITHIUM-ION

DTW1004



DTW1001



DTW1002



DTW800

DTW1004

12.7mm (1/2")

Pin-detent Squaredrive



Max fastening
torque
1,050N·m

DTW1001

19mm (3/4")

Crimg Squaredrive



Max fastening
torque
1,250N·m

DTW1002

12.7mm (1/2")

Crimg Squaredrive



Max fastening
torque
1,200N·m

DTW800

11.1mm (7/16")

hex shank bit holder



Max fastening
torque
800N·m





**BL
MOTOR**

XPT

Twin LED job light
(with preglow and
afterglow functions)



Variable speed control
by trigger

Electronic 3 stage
impact power selection



Hanging ring
(DTW800 only)



Forward/reverse push
button switch

Ergonomically
designed handle with
rubberized soft grip

Hook for operator
convenience



Accessories

Socket assembly

model:
DTW1004 /
DTW1001 /
DTW1002



Protector



Extension handle set



Pin 4 set

model:
DTW1004



Charging Time

	Fast Charging DC18RC	DC18SD
BL1815N 1.5Ah	15 min	30 min
BL1820B 2.0Ah	24 min	45 min
BL1830B 3.0Ah	22 min	60 min
BL1840B 4.0Ah	36 min	90 min
BL1850B 5.0Ah	45 min	110 min
BL1860B 6.0Ah	55 min	130 min

Cordless Impact Wrench

DTW1004 1/2" (12.7mm) / DTW1001 3/4" (19mm) / DTW1002 1/2" (12.7mm) / DTW800 7/16" (11.1mm)

	DTW1004	DTW1001	DTW1002	DTW800
Variable Speed	Fastening capacities Standard bolt: M12- M30(1/2- 1-1/4") High strength bolt (Grade10.9): M10- M20(3/8- 3/4")	Standard bolt: M12- M30(1/2- 1-1/4") High strength bolt: M10- M24(3/8- 1")	Standard bolt: M12- M30(1/2- 1-1/4") High strength bolt: M10- M24(3/8- 1")	Standard bolt: M12- M24(1/2- 1") High strength bolt: M10- M22(3/8- 7/8")
Brake	High strength bolt (Grade F10T): M16- M24(5/8- 1")			
Reversing	Square drive 12.7mm (1/2")	19mm (3/4")	12.7mm (1/2")	11.1mm (7/16")
Electronic 3-Speed	Max fastening torque Nut-busting torque 1,050N·m (780ft.lbs.) 1,300N·m (960ft.lbs.)	1,250N·m (920ft.lbs.) 1,700N·m (1,250ft.lbs.)	1,200N·m (890ft.lbs.) 1,600 N·m (1,180ft.lbs.)	800N·m (590ft.lbs.) -
Built-in Job Light	No load speed (RPM) Impact per minute (IPM) Hard/Med./Soft: 0-2,000/0-1,000/0-900 Hard/Med./Soft: 0-2,400/0-2,000/0-1,800	Hard/Med./Soft: 0-1,800/0-1,000/0-900 Hard/Med./Soft: 0-2,200/0-2,000/0-1,800	Hard/Med./Soft: 0-1,800/0-1,000/0-900 Hard/Med./Soft: 0-2,200/0-2,000/0-1,800	Hard/Med./Soft: 0-1,800/0-1,000/0-900 Hard/Med./Soft: 0-2,200/0-2,000/0-1,800
Carrying Case	Impact tightening of fasteners of the maximum capacity of the tool: 18.4m/s² Vibration level Sound pressure level 98 dB(A) Sound power level 106 dB(A) Dimensions (L x W x H) w/ BL1830B/ BL1840B/ BL1850B/ BL1860B: 229 x 91 x 289 mm (8-3/4 x 3-5/8 x 11-3/8") Net weight 3.1- 3.4kg (6.8- 7.5lbs.)	Impact tightening of fasteners of the maximum capacity of the tool: 15.5m/s² 101 dB(A) 109 dB(A) w/ BL1830B/ BL1840B/ BL1850B/ BL1860B: 229 x 91 x 289 mm (9x3-5/8 x 11-3/8") 3.4- 3.7kg (7.5- 8.2lbs.)	Impact tightening of fasteners of the maximum capacity of the tool: 18m/s² 100 dB(A) 108 dB(A) w/ BL1830B/ BL1840B/ BL1850B/ BL1860B: 229 x 91 x 289 mm (9x3-5/8 x 11-3/8") 3.3- 3.6kg (7.3- 8lbs.)	Impact tightening of fasteners of the maximum capacity of the tool: 24m/s² 98 dB(A) 106 dB(A) w/ BL1830B/ BL1840B/ BL1850B/ BL1860B: 229 x 91 x 303 mm (9x3-5/8 x 11-7/8") 3.4- 3.7kg (8.2- 7.5lbs.)

Standard Equipment : DTW1001JX3: Tool + Shoulder belt: 161347-8(1), Connector plastic case (type 3): 821551-8(1), Inner tray: 837645-9(1), Battery BL1830B set: 197605-6(2), FAST CHARGER: DC18RC(1) || DTW1001RTE: BL1850(2), FAST CHARGER: DC18RC(1) || DTW1001Z: Tool



Makita Power Tools India Pvt. Ltd.
Unit II, Sy. Nos. 93/3 & 93/4, Koralur Village, Kasaba Hobli,
Hoskote Taluk, Bengaluru - 560067

Email: info@makita.in

Website: www.makita.in