





For Various Applications











UNISTRUT™









Accessories

Tool hanger Part No. 199296-9 (DCS553 only)





T.C.T. Saw Blade

Size: 150mm x 20mm Size: 136mm x 20mm No. teeth | Part No. B-07319 Metal 32T B-46296 Thin sheet metal B-47008 Thin sheet metal B-07325 SUS/Metal B-23117 B-40331

| Cordless Metal Cutter | DCS553 150 mm (5-7/8") | | DCS552 136 mm (5-3/8") | 430 |
|-----------------------|---|---|---------------------------------|-----|
| | | DCS553 | DCS552 | |
| № Brake | Blade Diameter | 150 mm (5-7/8") | 136 mm (5-3/8") | |
| | Max Cutting Capacity | 90°: 57.5 mm (2-1/4") | 90°: 50.5 mm (2") | |
| Built-in Job Light | No Load Speed (RPM) | 4,200 | 3,600 | |
| <u></u> | Vibration Level | Cutting Metal: 2.5 m/s ² or less | Cutting Metal: 2.5 m/s² or less | |
| Carrying Case | Sound Pressure Level | 103 dB(A) | 102 dB(A) | |
| | Sound Power Level | 114 dB(A) | 113 dB(A) | |
| | Dimensions (L x W x H) | 267x186x250 mm | 348x196x203 mm | |
| | | (10-1/2"x7-3/8"x9-7/8") | (13-3/4"x7-3/4"x8") | |
| | Net weight | 2.8 - 3.1 kg (6.1 - 6.8 lbs.) | 2.4 - 2.7 kg (5.3 - 6.0 lbs.) | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | Standard Equipment: TCT Saw Blade, Hex Wrench, Safety Goggles, Battery, Charger | | | |

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 201808





Max cutting capacity 57.5_{mm}







136mm TCT saw blade

Self-Dust Collection Box for less dust leakage



DCS553

Max work amount


125 cuts

- with BL1850B
- Carbon steel pipe of 34mm diameter with thickness of 3.2mm

Easy disposal of dust by simply opening Dust cap.

(DCS553 / DCS552)







Battery fuel gauge (DCS553 only)




DCS553

Compact design

Overall length of the tool has been greatly shortened by relocating battery.



Predecessor Model 332mm



65_{mm} **Shortened**

Automatic speed

automatically changes the cutting mode according to load conditions for an optimum operation:

