

Satisfy Professional's Needs



Cordless Driver Drill
Cordless Hammer Driver Drill
DDF485 13 mm (1/2") / DHP485 13 mm (1/2")



Photo: DDF485

More compact
More speed
More power

Max lock torque
50 N·m

Cordless Driver Drill

DDF485



Cordless Hammer Driver Drill

DHP485



Hi-speed Max. 1,900 RPM



Compact overall length

DDF485: 169mm, DHP485: 182mm
Predecessor Model: 179mm, 192mm

Single sleeve keyless chuck

allows for easy bit installation/removal by one hand.

Capacity of drill chuck

1.5mm (1/16") - 13mm (1/2")

21 Torque settings



Twin LED job light with preglow and afterglow functions



Variable speed control by trigger

Photo: DHP485

Mechanical 2-speed gearing



Ergonomic handle with soft grip for driver-drill applications

- In order to provide maximum thrust to the bit, the top back of the handle is ergonomically contoured and widened to perfectly fit the U-shape formed between user's thumb and index finger.
- Newly designed slimmer grip provides comfortable grip with less fatigue.



Belt clip



Accessory

Tool catcher set

Enables to hook the machine quickly on a snap hook of waist belt.



Part No. 197043-2



Cordless Hammer Driver Drill DHP484



Cordless Driver Drill DDF484



Cordless Driver Drill		DDF485 13 mm (1/2")	
Cordless Hammer Driver Drill		DHP485 13 mm (1/2")	
Variable Speed		DDF485	DHP485
Brake			
Reversing			
Mechanical 2-Speed			
Keyless Chuck			
Torque Setting 21			
Built-in Job Light			
Carrying Case			
Standard Equipment:			
Belt Clip, (+/-) Bit, Battery, Charger			
		Capacity	Steel / Wood: 13 / 38 mm (1/2" / 1-1/2")
		Chuck capacity	1.5 - 13 mm (1/16 - 1/2")
		Impacts Per Minute (IPM)	High / Low: 0 - 28,500 / 0 - 7,500
		No Load Speed (RPM)	High / Low: 0 - 1,900 / 0 - 500
		Max Fastening Torque	Hard / Soft: 50 / 27 N·m (440 / 240 in.lbs.)
		Max lock torque	50 N·m (440 in.lbs.)
		Max Output	350 W
		Clutch torque setting	1.0 - 5.0 N·m (9 - 44 in.lbs.)
		Vibration Level	Drilling Into Metal: 2.5 m/s ² or less
		Vibration Level	Hammer Drilling into Concrete: 8.0 m/s ²
		Sound Pressure Level	Drilling Into Metal: 2.5 m/s ² or less
		Sound Power Level	82 dB(A)
		Dimensions (L x W x H)	93 dB(A)
			w/ BL1815N / BL1820B: 169x79x237 mm (6-5/8"x3-1/8"x9-3/8")
			w/ BL1830B / BL1840B / BL1850B / BL1860B: 169x79x255 mm (7-1/8"x3-1/8"x10")
			w/ BL1815N / BL1820B: 182x79x237 mm (7-1/8"x3-1/8"x9-3/8")
			w/ BL1830B / BL1840B / BL1850B / BL1860B: 182x79x255 mm (7-1/8"x3-1/8"x10")
		Net weight	1.5 - 1.8 kg (3.2 - 3.9 lbs.)
			1.4 - 1.7 kg (3.1 - 3.8 lbs.)

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 201809