



Satisfy Professional's Needs

# Cordless Rotary Hammer DHR165 / DHR164 16mm (5/8")



Adapted for  
SDS-PLUS bit



## Lightweight and compact design



Hammering  
with  
Rotation

# 2

mode



Rotation



Photo: DHR165

Tool does not come with bit.



# Ergonomic handle for perfect tool control and minimum hand fatigue and pain.



Adapted for SDS-PLUS bit


Compact **297 mm (11-3/4")**

Ribbed soft grip



In-line positive grip design maximizes power thrust.

One touch sliding chuck for easy bit changes



Torque limiter

Reverse switch

Variable speed control by trigger



Single-light LED job light with afterglow function

- On pulling switch trigger, the light automatically turns on before motor starts turning.
- keeps on illuminating about 12-13 sec. after trigger release

Photo : DHR165

**XPT**  
EXTREME PROTECTION TECHNOLOGY

## Power by Li-ion batteries

DHR165



BL1850 (5.0Ah), BL1840 (4.0Ah), BL1830 (3.0Ah), BL1820 (2.0Ah), BL1815N (1.5Ah)

DHR164



BL1440 (4.0Ah), BL1430 (3.0Ah), BL1430A (3.0Ah), BL1415NA (1.5Ah)

## Charger

DC18RC



Two Port Multi Fast Charger DC18RD



Charging time (3.0Ah) 22minutes

Four Port Multi Charger DC18SF

Charging time (4.0Ah)  
1 to 2 batteries : 90minutes  
3 to 4 batteries : 180minutes



DC18SD  
Charging time (4.0Ah) 90minutes



DC18SE (Automotive)  
Charging time (4.0Ah) 90minutes



Lightweight

**2.2kg**

(4.9lbs)

DHR165 with BL1815N



Photo : DHR164

## Cordless Rotary Hammer

**DHR165 / DHR164 16mm (5/8")**

430

- Variable Speed
- Brake
- Reversing
- SDS-PLUS Shank
- Torque Limiter
- Dust Collecting
- Built-in Job Light
- Carrying Case

	<b>18V LITHIUM-ION</b> DHR165	<b>14.4V LITHIUM-ION</b> DHR164
<b>Capacity</b>	Concrete : 16mm (5/8") Steel : 13mm (1/2") Wood : 24mm (15/16")	Concrete : 16mm (5/8") Steel : 13mm (1/2") Wood : 24mm (15/16")
<b>Impacts per minute (ipm)</b>	0 - 5,300	0 - 5,300
<b>No load speed (rpm)</b>	0-1,600	0-1,600
<b>Dimensions (L x W x H)</b>	BL1830, BL1840, BL1850: 297x79x253mm (11-3/4"x3-1/8"x10") BL1815N, BL1820: 297x79x236mm (11-3/4"x3-1/8"x9-1/4")	BL1430, BL1430A, BL1440: 297x79x250mm (11-3/4"x3-1/8"x9-7/8") BL1415NA, BL1415N: 297x79x235mm (11-3/4"x3-1/8"x9-1/4")
<b>Net weight</b>	BL1830, BL1840, BL1850: 2.5kg (5.5lbs) BL1815N, BL1820: 2.2kg (4.9lbs)	BL1430, BL1430A, BL1440: 2.4kg (5.3lbs) BL1415NA, BL1415N: 2.2kg (4.8lbs)

Tool does not come with bit.

Standard Equipment : Fast charger, Battery cartridge, Side grip, Depth gauge

weight according to EPTA-Procedure 01/2003

Items of standard equipment and specifications may vary by country or area.

**Makita Corporation**

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN BE-BA