



Cordless Slide Compound Miter Saw
DLS714 190mm (7-1/2")



Powered by two 18V Li-ion batteries in series

	45° Bevel Cut at 45° left	Cross Cut	5° right
Miter at 0° With a 20mm (3/4") auxiliary wood fence	 45x265 (1-3/4" x 10-3/8") 40 x 300 mm (1-9/16" x 11-3/4")	 60x265 (2-3/8" x 10-3/8") 52 x 300 mm (2-1/16" x 11-3/4")	 40 x 300 mm (1-9/16" x 11-3/4")
Miter at 45° With a 15mm (3/5") auxiliary wood fence	 45x185 (1-3/4" x 7-1/4") 40 x 212 mm (1-9/16" x 8-3/8")	 60x185 (2-3/8" x 7-1/4") 52 x 212 mm (2-1/16" x 8-3/8")	-
Miter at 57° With a 10mm (3/8") auxiliary wood fence	-	 60x145 (2-3/8" x 5-3/4") 52 x 163 mm (2-1/16" x 6-3/8")	-


Optional Accessories

- Fast Charger DC18RC
- Charger DC18SD
- Fast Charger DC18RD Two Port Multi Fast Charger
- Stand set Part No. WST06



TCT Saw Blade
Blade dia. 190mm
Hole dia. 20mm

Tip (mm)	Hook angle (dig)	No. teeth	Part No.
2.2	5	24	B-03850
2.0	-5	24	B-03866
2.0	10	40	A-86751
2.0	5	60	B-04008
2.0	-5	60	B-03981
2.0	10	72	A-86359



Cordless Slide Compound Miter Saw DLS714 190mm (7-1/2")

- Brake
- Soft Start
- Bevel Cutting L45 R5
- Dust Collection

Max. cutting capacity	at 0 degrees: 52x 300mm (2-1/16" x 11-3/4") at 45 degrees: 52x 212mm (2-1/16" x 8-3/8") at 57 degrees: 52x 163mm (2-1/16" x 6-3/8")
Blade diameter	190mm (7-1/2")
No load speed (rpm)	5,700
Dimensions (L x W x H)	655 x 430 x 445mm (25-3/4" x 17" x 17-1/2")
Net weight*	European countries: BL1820 13.0kg (28.7lbs) BL1850 13.5kg (29.8lbs) Other countries : BL1820 12.6kg (27.8lbs) BL1850 13.1kg (28.9lbs)

Standard Equipment
DLS714Z: Vise assembly: 122571-8(1), Dust bag assembly: 122852-0(1), Triangular rule: 762001-3(1), Hex. wrench 5: 783217-7(1), T.C.T.SAW BLADE 190X20X24: B-03850(1), Holder 322312-4(2)



High power delivered by 36V (18Vx2)
DC Brushless motor enables to cut as fast as if you were using a corded slide compound miter saw.

