Satisfy Professional's Needs

makita®

Cordless Impact Driver DTD153

LXT LITHIUM-ION

High Performance with Brushless DC Motor.

Max tightening torque

170N·m

Lightweight at

1.3kg

(BL1815N)

18V LITHIUM-ION

BL MOTOR

Aluminum hammer case
createsimpression of rigidity.

One-touchbit installation
(For some countries only)
No need to pull bit sleevefor bit installation

Twin LEDJoblight with pre-glow and afterglow functions

High rotational speed
3,400
rpm

Belt clip

Variable speed control by trigger

Ergonomically designed handle with soft grip
providescomfortable grip and more control while minimizing hand fatigue and pain.

Powered by
18V Li-ion batteries

Optional Accessories

Tool catcher set

enablesto hook the machine quickly on a snap hook of waist belt.



Part No. 197043-2

Battery Protector

designedto protect the battery cartridge from dust and dripping water in outdoor applicationsor harsh environments.

Part No. 195798-3

Battery / Charger

with Battery fuel gauge

18V LITHIUM-ION

*without Batteryfuel gauge

BL1860B(6.0Ah)
BL1850B(5.0Ah)
BL1840B(4.0Ah)
BL1830B(3.0Ah)
BL1820B(2.0Ah)
*BL1815N (1.5Ah)

Fastcharger
DC18RC

Charger
DC18SD

Cordless Impact Driver

DTD153

- Variable Speed
- Brake
- Reversing
- Built-in Job Light

Capacity	Machinescrew :	M4 - M8 (5/32" - 5/16")
	Standardbolt :	M5 - M16 (3/16" - 5/8")
	High strength bolt:	M5 - M14 (3/16" - 9/16")
	Coarsethread (in length) :	22 - 125mm (7/8" - 4-7/8")
Impactsper minute(ipm)		0 - 3,600
No load speed(rpm)		0 - 3,400
Max. fastening torque		170 N·m(1,500 in·lbs)
Vibration Level		13.0 m/s²
Sound Pressure Level		96 dB(A)
Sound Power Level		107 dB(A)
Dimensions(L x Wx H)		126x79x238mm(5"x3-1/8"x9-3/8")
Net weight		BL1850B: 1.5kg (3.3lbs)
		BL1815N: 1.3kg (2.8lbs)

Standard Equipment :
DTD153Z: Hook 346317-0(1)
DTD153RFE: Plastic case: 141856-3(1), Hook: 346317-0(1), Battery BL1830B: 197605-6(2), DC18RC FAST CHARGER DC18RC(1)