




# Cordless Angle Impact Wrench

DTL063 3/8" (9.5 mm)

## 18V LXT Li-Ion Cordless 3/8" (9.5 mm) 60 N·m Angle Impact Wrench



### Cordless Angle Impact Wrench



Variable Speed



Brake



Reversing



Built-in Job Light

Fastening Capacities	Standard Bolt: M4 - M12 (5/32" - 1/2") High Strength Bolt: M4 - M8 (5/32" - 5/16")
Square Drive	9.5 mm (3/8")
No Load Speed (RPM)	0 - 2,000
Impacts Per Minute (IPM)	0 - 3,000
Max Fastening Torque	60 N·m (N/A ft.lbs.)
Sound Pressure Level	88 dB(A)
Sound Power Level	99 dB(A)
Noise K Factor	3 dB(A)
Dimensions (L x W x H)	387x78x116mm (15-1/4"x3-1/16"x4-9/16")
Net weight VV	1.4 - 2.0 kg (3.1 - 4.3 lbs.)

Standard Equipment : DTL063Z: Hook: 346317-0(1)



Makita Power Tools India Pvt. Ltd.

Unit II Sy. Nos. 93/3 & 93/4, Koralur village, Kasaba Hobli, Hoskote Taluk,  
Bangalore - 560 067, INDIA. Tel: +91 80 2854 9008, Fax: +91 80 2854 9007  
Email: sales@makita.in Website: www.makita.in