



Cordless Impact Wrench
DTW190 1/2" (12.7mm)



Maximum tightening torque*
190 N·m (140 ft·lbs)



* Tightening torque at 6 seconds after seating, when tightening M16 (grade 10.9) high strength friction grip bolt.

Shoulder strap & tool catcher as optional accessories



Compact and light weight

18V
LITHIUM-ION

1/2"(12.7mm) Square drive

LED Job light with preglow function

On pulling switch trigger, the light automatically turns on before motor starts turning.



Variable speed control by trigger

Ergonomically designed handle with rubberized soft grip

provides comfortable grip and more control while minimizing hand fatigue and pain.

Belt clip can be attached. (option)



Tool catcher (option)



Shoulder strap (option)
improves freedom of operator's movement during work at height.

Part No. 197676-3
(with tool catcher)



18V Li-ion battery

with Battery fuel gauge

BL1860B: 6.0Ah

BL1850B: 5.0Ah

BL1840B: 4.0Ah

BL1830B: 3.0Ah

BL1820B: 2.0Ah

BL1815N: 1.5Ah

(without Battery fuel gauge)



Fast Charger

DC18RC



Charger

DC18SD



Cordless Impact Wrench

DTW190 1/2" (12.7mm)

- Variable Speed
- Brake
- Reversing
- Built-in Job Light
- Carrying Case

Capacity

Standard bolt: M8 - M16 (5/16" - 5/8")

High strength bolt: M8 - M12 (5/16" - 1/2")

Square drive: 12.7mm (1/2")

Impacts per minute (ipm)

0-3,000

No load speed (rpm)

0-2,300

Max Fastening Torque

190 N·m (140ft·lbs)

Dimensions (LxWxH)

176x79x237mm (6-15/16"x3-1/8"x9-3/8")

Net weight

BL1820B: 1.4kg (3.2lbs)

BL1850B: 1.7kg (3.7lbs)

Standard Equipment: Battery cartridge, charger

(Tool does not come with socket.)

weight according to EPTA-Procedure 01/ver.2.1
Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 201602