This movie was filmed in Japan. Models and specs may vary by country.



18V X2 Lithium-ion

Powered by two 18V Li-ion batteries in series







Chain Sav

Cordless Mult DLM431 / DLM380 DUX60

Grass Tri Function Power Head DUR361U / DUR365U

Grass Tr DUR362L / DUR364L DUR366I

DUC303 / DUC353 / DUB361 / DUB362 DUC400 / DUC252 / DUC302 / DUC252C

Hedge Tr Battery P DUP361 DUH551 / DUH651



Li-ion Battery & Charging Time Reference, **Compatibility Chart**

TIBV United and form	DC18RD
BL1815N 1.5Ah	15 min
BL1820B 2.0Ah	24 min
BL1830B 3.0Ah	22 min
BL1840B 4.0Ah	36min
BL1850B 5.0Ah	45 min
BL1860B 6.0Ah	55 min

DUX60

	Variable Speed
%	Brake
	Reversing
3	Electronic 3-Speed
\bigotimes	Constant Speed
5	Soft Start

No Load Speed (RPM) High: 0 - 9,700 Medium: 0 - 8,200 Low: 0 - 5,700 Dimensions (L x W x H) 1,011x320x216 mm (39-3/4"x12-5/8"x8-1/2") 4.1 - 8.7 kg (8.9 - 19.2 lbs) Net weigh

Standard Equipment

Harness, Safety Goggles, Hex Wrench, Accessory Bag, Tool bag (for spec with Brushcutter attachment only), Carbide-Tipped Saw Blade (for spec with EM402MP only), Box Wrench (for spec with EM402MP/EM403MP/EM404MP only), Metal blade fixing tool (Clamp washer, Nut, Cup) (for spec with EM402MP/EM403MP/EM404MP), Nylon Cutting Head (for spec with EM403MP/EM404MP), Nylon Cutting Head (for spec with EM403MP/EM404MP/EM405MP/EM406MP only), Battery, Charger

> The weight may differ depending on the attachment(s), including the battery cartridge The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area

Power Head DUX60







3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

Makita Corporation

PRINTED IN JAPAN 201802

Satisfy Professional's Needs

Cordless Multi Function



One for All All for One

Wide range of attachments



High power similar to 25mL petrol tool

This movie was filmed in Japan. Models and specs may vary by country.



High Power BL Motor Enables to Work under Heavy Load

BL Motor provides high operating efficiency





Active Feedback sensing Technology

turns the motor off if rotation speed suddenly slows down



AF



Reverse switch for easy removal of grass clippings from the cutting tool

Grass clippings can be removed by slow reverse rotation of the cutting tool (automatically stops in 3 seconds) by pressing touch button switch and pulling trigger switch.



Easy Change

Lever style lock system allows for quick toolless installation and replacement of the attachments.

Excellent Mobility

Split system of Power head and Attachment provides easier mobility. Optional tool bag makes it even easier to transport and for storage.



Extreme Protection Technology

For use in outdoor applications or harsh environments, protection from dust and dripping water is enhanced.





Optional attachments





















