



Cutter
4100NH3 110mm (4-3/8")



Smoother operation
with grooved base plate back surface

Redesigned base with grooved back surface for smoother operation.

The grooves added on the back surface of the base reduce the resistance caused by surface tension of water to prevent the base from adhering to the surface of workpiece in wet applications.



Flat rear end is convenient for replacing the diamond wheel.



Anti-slip dimples

On-tool storage for hex wrench

Easy alignment of base end with the cutting line on workpiece.

Water supply fixture can be mounted.

1,200W


continuous rating input



Cutter

4100NH3 110mm (4-3/8")

303

 Double Insulation

Standard Equipment:

Wrench, Hex Wrench, Water supply fixture (for some countries)
(Tool does not come with diamond wheel.)

Continuous rating Input	1,200W
Capacity	Max. cutting : 32 mm (1-1/4")
Blade diameter	110 mm (4-3/8")
No load speed (rpm)	13,000
Dimensions (L x W x H)	227x209x166mm (8-15/16"x8-1/4"x6-1/2")
Net Weight*	2.9kg (6.4lbs)
Power supply cord	2.0m (6.6ft)

*weight according to EPTA-Procedure 01/2003 *Items of standard equipment and specifications may vary by country or area.*

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN BD-AI