



Satisfy Professional's Needs

Screwdriver series

Easy handling and High maneuverability



FS2500

The image shows a teal Makita FS2500 screwdriver with a black handle and a silver-colored motor housing. It is positioned diagonally on a corrugated metal surface.

FS2701

The image shows a teal Makita FS2701 screwdriver with a black handle and a silver-colored motor housing. It is positioned diagonally on a corrugated metal surface.

FS2700

The image shows a teal Makita FS2700 screwdriver with a black handle and a silver-colored motor housing. It is positioned diagonally on a corrugated metal surface.

Best possible tool body for screwdriving.



FS2500



Optimum for fastening teks or hex screw.

One touch locator
Easy to install or remove

Ingenious exhaust vents
Exhaust air does not blow dust and debris around when the tool is used close to floor level.

Reversing switch

Variable speed control by trigger switch

More durable belt clip composed of a sheet metal sandwiched between plastic layers for added strength

Best possible tool body for screwdriving ergonomically designed to;
- minimize hand fatigue and pain even in long continuous operation.
- give maximum power thrust.
- allow for much smoother and easier trigger pull.



Rubberized soft grip provides comfortable grip and more control while minimizing hand fatigue and pain.

LED job light convenient for operation in dark job sites



Bit holder
Spare bit can be stored.

FS2700

Removal front cap for changing from self-drilling screws to hex bolts operation.

6 Stage torque adjustment for a wide range of applications.

FS2701

Bit sleeve for easy bit change.

6 Stage torque adjustment for a wide range of applications.

Accessories

Locator (for Model FS2500)
For Magnetic socket bit



Front cap (for Model FS2700)



For bit size	Part No.	
1/4"	450963-4	
5/16"	450967-6	
3/8"	450968-4	

For Phillips bit L=45mm (type NZ)

Size	Part No.	
12	322070-2	

For Magnetic bit holder + Phillips insert bit (type MZ)

Size	Part No.	
12	322263-1	

For Socket bit (type NZ)

Size	Part No.	
15.5	322069-7	

For Magnetic Socket bit L=50mm (type MZ)

Size	Part No.	
-	322120-3	

For Magnetic Socket bit L=65mm (type MZ)

Size	Part No.	
1/4"	322124-5	
5/16"	322125-3	
3/8"	322119-8	
7/16"	322126-1	

Locator assembly (for Model FS2500)
For Magnetic bit holder + Phillips insert bit



Type	Part No.	
Short	122867-7	
Long	122868-5	

Screwdriver FS2500/ FS2700/ FS2701

Screwdriver	FS2500/ FS2700/ FS2701			
	FS2500	FS2700	FS2701	
Double Insulation	570W			
Variable Speed	570W			
Reversing	570W			
Built-in Job Light	570W			
Torque Setting 6 (FS2700, FS2701)	570W			
Continuous rating Input	570W	570W	570W	
Capacity Drywall screw:	5mm (3/16")	6mm (1/4")	6mm (1/4")	
Self drilling screw:	6mm (1/4")	6mm (1/4")	6mm (1/4")	
Hex. screw:	-	6mm (1/4")	6mm (1/4")	
Driving shank (Hex.)	6.35 mm (1/4")	6.35mm (1/4")	6.35mm (1/4")	
No load speed (rpm)	0-2,500	0-2,500	0-2,500	
Dimensions** (L x W x H)	280 x 70 x 207mm (11" x 2-3/4" x 8-1/8")	301 x 70 x 207mm (11-7/8" x 2-3/4" x 8-1/8")	283 x 70 x 207mm (11-1/8" x 2-3/4" x 8-1/8")	
Net weight*	1.5kg (3.4lbs)	1.8kg (4.0lbs)	1.7kg (3.8lbs)	
Power supply cord	2.5m (8.2ft)	2.5m (8.2ft)	2.5m (8.2ft)	

Standard Equipment Magnetic Socket Bit (FS2500 only)

**for countries providing noise suppressor
*weight according to EPTA-Procedure 01/2003

Items of standard equipment and specifications may vary by country or area.



Makita Power Tools India Pvt. Ltd.
Unit II Sy. Nos. 93/3 & 93/4, Koralur village, Kasaba Hobli, Hoskote Taluk,
Bangalore - 560 067, INDIA. Tel: +91 80 2205 8200, Fax: +91 80 2854 9007
Email: sales@makita.in Website: www.makita.in

