

Durable shaft lock

Re-designed durable shaft lock firmly supported by metal sleeve built in gear housing prevents cracks in gear housing and drop of pin cap.

Soft Start

Minimizes start-up shock, and makes the tool start smoothly.



Photo : GA4541R

Dust collecting wheel guard



for set diamond wheel.

Part No.
195238-1
195239-9
196575-6



for diamond wheel.

Part No.
196845-3

Part No. vary by country or area



Toolless wheel cover (Option)

Toolless wheel cover is adjustable to any desired position without tool. (Component for some countries or models, also available as option)



Ezy nut (Option)

Ezy nut (tool-less lock nut) is available as an option for the models with M14 spindle to replace wheel without wrench.



Anti-vibration grip (Option)

for extra comfort

Angle Grinder (with Anti-restart function)		without Brake			with Brake	
Double Insulation						
Soft Start						
MODEL	115mm GA4540R	125mm GA5040R	150mm GA6040R	115mm GA4541R	125mm GA5041R	
Continuous rating Input	1,100W	1,100W	1,100W	1,100W	1,100W	
Wheel diameter	115mm (4-1/2")	125mm (5")	150mm (6")	115mm (4-1/2")	125mm (5")	
No load speed (rpm)	11,000	9,000	9,000	11,000	11,000	
Dimensions (L x W x H)	303x130x116mm (11-7/8"x5-1/8"x4-9/16")	303x140x116mm (11-7/8"x5-1/2"x4-9/16")	303x171x116mm (11-7/8"x6-3/4"x4-9/16")	303x130x116mm (11-7/8"x5-1/8"x4-9/16")	303x140x116mm (11-7/8"x5-1/2"x4-9/16")	
Net Weight*	2.4kg (5.4lbs)	2.5kg (5.4lbs)	2.5kg (5.6lbs)	2.6kg (5.8lbs)	2.7kg (5.9lbs)	
Power supply cord	2.5m (8.2ft)	2.5m (8.2ft)	2.5m (8.2ft)	2.5m (8.2ft)	2.5m (8.2ft)	

Standard Equipment : Depressed Center Wheel, Lock Nut Wrench, Side Grip, Anti-vibration grip, Diamond wheel, Connector plastic case

*weight according to EPTA-Procedure 01/2003 Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN BE-BC



Angle Grinder

GA4540R, GA5040R, GA6040R
GA4541R, GA5041R (with Brake)
115mm (4-1/2"), 125mm (5"), 150mm (6")

Satisfy Professional's Needs

1,100W



SJS II

Drastic Evolution of Vibration Absorption

with Anti-restart function series

