



Angle Grinder





GA5020C 125 mm (5")


High power and devised switch with electric control



Angle Grinder



-  Double Insulation
-  Constant Speed
-  Soft Start
-  Dust Collection

Continuous rating input	1,450W	253 
Wheel Diameter	125 mm (5")	
No Load Speed (RPM)	10,000	
Vibration Level	Surface Grinding: 9.5 m/s ²	
Vibration K Factor	Surface Grinding: 1.5 m/s ²	
Vibration Level	Disc Sanding: 2.5 m/s ² or less	
Vibration K Factor	Disc Sanding: 1.5 m/s ²	
Sound Pressure Level	90 dB(A)	
Sound Power Level	101 dB(A)	
Noise K Factor	3 dB(A)	
Dimensions (L x W x H)	390x139x120 mm (15-3/8"x5-1/2"x4-3/4")	
Net weight	2.9 - 4.1 kg (6.5 - 9.1 lbs.)	
Power supply cord	2.5 m (8.2 ft)	

Standard Equipment: Depressed Center Wheel, Side Grip, Wheel Cover, Lock Nut Wrench



Makita Power Tools India Pvt. Ltd.

Unit II Sy. Nos. 93/3 & 93/4, Koralur village, Kasaba Hobli, Hoskote Taluk,
Bangalore - 560 067, INDIA. Tel: +91 80 2854 9008, Fax: +91 80 2854 9007
Email: sales@makita.in Website: www.makita.in