

Angle Grinder GA7030/ S, GA7040/ S 180mm (7") GA9030/ S, GA9040/ S 230mm (9")

Outstanding Durability















Angle Grinder GA7030/ S/ GA7040/ S 180mm (7") / GA9030/ S/ GA9040/ S 230mm (9")







		1		
	GA7030/ GA7030S	GA7040/ GA7040S	GA9030/ GA9030S	GA9040/ GA9040S
Continuous rating Input	2,400W	2,600W	2,400W	2,600W
Capacity (Depressed center wheel)	180mm (7")		230mm (9")	
Hole dia.	22.23mm (7/8")		22.23mm (7/8")	
No load speed	8,500rpm		6,600rpm	
Dimensions (L x W x H)	511mm x 200mm x 140mm (20-1/8" x 7-7/8" x 5-1/2")		511mm x 249mm x 140mm (20-1/8" x 9-3/4" x 5-1/2")	
Net weight*	6.0kg (11.2lbs)	6.4kg (14.0lbs)	6.3kg (13.9lbs)	6.6kg (14.6lbs) GA9040 6.7kg (14.8lbs) GA9040S
Power supply cord	2.5m (8.2ft)		2.5m (8.2ft)	
	1			

Standard Equipment: Lock Nut wrench, Grip (Tool does not come with depressed center wheel)

*weiaht according to EPTA-Procedure 01/2003

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN BD-AJ



The Inside of the Creature Is...

/// Large Rubber Tool Rest

Outstanding Durability

/// Superior Anti-Dust Structure

Protective zigzag varnish on armature coil. Protective powder vanish-coating on field coil. Bearing-protective labyrinth construction. Vent slots designed to minimize dust entrance.



/// Machined Bevel Gear

having durability higher than sintered gear.

/// Increased Heat Resistance superior to our predecessor

///Torque Limiter

models.

/// Rotatable Rear Handle

Can be positioned to suit most cutting and grinding operations. (90 degrees R/L)







/// Large-boned shaft having durability

Zigzag varnish

powder vanish-coating

/// Heavy Duty Motor

180mm (7") **GA7030/ S** 2,400W

230mm (9") GA9030/ S 2,400W

GA7040/ S 2,600W

GA9040/S 2,600W

///Low Vibration Rear Handle

with soft grip for more comfort and control.



///Vibration Absorbing Side Grip (option)

