



Satisfy Professional's Needs

Straight Grinder

GS5000 125mm (5") / **GS6000** 150mm (6")



Photo: GS6000

GS5000 125mm (5")

GS6000 150mm (6")

Ergonomically design handle and barrel for added extra maneuverability.

Lightweight with large soft grip reduce operator's fatigue.

Ergonomically design barrel
with rubberized cover



Improved durability of gears
about two times as tough as the current by;

- (1) Change of the grease
- (2) Modification on the inside of Gear housing for grease to stay on Gears teeth.

Dust cover attachment set
(optional accessory)
Part No. 195059-1
protect motor from metal dust.



Photo: GS6000

Rubberized soft grip
provides comfortable and sure grip.

Large type trigger switch



with a lever for lock-off and lock-on in compliance with the requirement** of the new IEC regulations (for Europe)

By pushing the lever forward, the switch is released from Lock-off position. By pulling the lever backward, the switch is locked on.

**The lock lever is required to have two different actions for releasing the switch from Lock-off position and locking the switch on.

Auto Cut-out Carbon Brush

Automatically stops the motor to protect commutator when carbon brush wears out.

Hanger bracket
(optional accessory)

Part No. 342004-9
can be attached for continuous use with less fatigue.



Use with Pan head screw M5x16 2pcs.

Wheel cover in compliance with the regulations.

Accessories

Grinding wheel

(EN): EN 12413

* ANSI B71



Double Insulation

Size (mm)	Grit	General Label	North America Label
		Part No.	Part No.
For Model: GS5000			
125 x 20 x 12.7	A24P	B-33990	-
125 x 20 x 12.7	A36P	B-34001	-
125 x 20 x 20	A24P	-	B-34039
125 x 20 x 20	A36P	-	B-34045
125 x 20 x 20	A24P	B-28662 (EN)	B-28852*
125 x 20 x 20	A36P	B-28678 (EN)	B-28868*
For Model: GS6000			
150 x 20 x 12.7	A24P	B-34017	-
150 x 20 x 12.7	A36P	B-34023	-
150 x 20 x 20	A24P	-	B-34051
150 x 20 x 20	A36P	-	B-34067
150 x 20 x 20	A24P	B-28684 (EN)	B-28874*
150 x 20 x 20	A36P	B-28690 (EN)	B-28880*

Straight Grinder

GS5000 125mm (5") / GS6000 150mm (6")

204

	GS5000	GS6000
Continuous rating Input	750W	750W
Wheel diameter	125mm (5")	150mm (6")
Hole dia.	12.7mm (1/2"), 20mm (3/4")	12.7mm (1/2"), 20mm (3/4")
No load speed (rpm)	5,600	5,600
Dimensions (L x W x H)	590x189x116mm (23-1/4"x7-7/16"x4-9/16")	590x216x130mm (23-1/4"x8-1/2"x5-1/8")
Net Weight*	5.0kg (11.1lbs)	5.2kg (11.5lbs)
Power supply cord	2.5m (8.2ft)	2.5m (8.2ft)

Standard Equipment :

Grinding Wheel (for some country only), Hex Wrench, Wrenches (for some country only)

*weight according to EPTA-Procedure 01/2003

Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN BD-AD