



Cordless Angle Impact Driver TL065D

Satisfy Professional's Needs

Ultra-Compact Angle Head

Ideal for Fastening in Tight Spots



Angle Impact Wrench
TL065D

Powered by Slide Li-ion Battery of Makita's New 12V max
Platform



Compact & Slim for Easy Handling

Head height
53mm

Center height
18mm

Max fastening torque
60 N·m


Lightweight
1.3kg
(2.8lbs.)
w/BL1016

Phosphorescent bumper


Belt clip

Photo : TL064D

For fastening and loosening in tight spaces



Angle wrench head



Single LED job light with preglow/ afterglow functions



Ergonomically designed handle with sure grip



Li-ion Battery & Charging Time Reference, Compatibility Chart

	DC10SB	DC10WD
*with Battery fuel gauge		
BL1016 1.5Ah	22 min	50 min
*BL1021B 2.0Ah	30 min	70 min
*BL1041B 4.0Ah	60 min	130 min

Accessories

Optional attachments for versatility

Angle head

Angle wrench head

Straight Head

Ratchet Head

Angle head
Part No. 135183-8
(For C-form bit)
Part No. 135200-4

Angle wrench head
9.5mm (3/8") square drive
Part No. 135201-2

Straight head
Part No. 192440-7
(For E-form bit)
Part No. 192486-3

Ratchet head
Part No. 192439-2

21mm

Socket adapter
Use with Ratchet head
9.5mm (3/8") square drive
Part No. 134745-9
12.7mm (1/2") square drive
Part No. 134746-7

Socket
Use with Ratchet head
Size: 17x 31
Part No. 134743-3
Size: 19x 33
Part No. 134744-1

Cordless Angle Impact Wrench TL065D

	TL064D
Variable Speed Brake Reversing Built-in Job Light Carrying Case	Capacity Machine Screw: M4 - M8 (5/32" - 5/16") Standard Bolt: M4 - M12 (5/32" - 1/2") High Tensile Bolt: M4 - M8 (5/32" - 5/16") Coarse thread (in length): 22 - 75mm (7/8" - 2-31/32") Hex Shank 6.35 mm (1/4") No Load Speed (RPM) 0 - 2,000 Impacts Per Minute (IPM) 0 - 3,000 Max Fastening Torque 60 N·m (530 in.lbs.) Vibration Level Impact tightening of fasteners of the maximum capacity of the tool: 15.0 m/s² Sound Pressure Level 91 dB(A) Sound Power Level 102 dB(A) Dimensions (L x W x H) 361x66x86mm (14-1/4"x2-5/8"x3-3/8") Net weight 1.3kg (2.8lbs.) - 1.6kg (3.6lbs.)
	TL065D
Variable Speed Brake Reversing Built-in Job Light Carrying Case	Capacity Standard Bolt: M4 - M12 (5/32" - 1/2") High Tensile Bolt: M4 - M8 (5/32" - 5/16") Square Drive 9.5 mm (3/8") No Load Speed (RPM) 0 - 2,000 Impacts Per Minute (IPM) 0 - 3,000 Max Fastening Torque 60 N·m (530 in.lbs.) Vibration Level Impact tightening of fasteners of the maximum capacity of the tool: 18.0 m/s² Sound Pressure Level 90 dB(A) Sound Power Level 101 dB(A) Dimensions (L x W x H) 361x66x86mm (14-1/4"x2-5/8"x3-3/8") Net weight 1.3kg (2.8lbs.) - 1.6kg (3.6lbs.)
Standard Equipment: Phillips Bit, Belt Clip, Battery, Charger	
Standard Equipment: Hook 346909-5(1); Plastic case 821709-9(1); Battery BL1016 set 198007-9(2); DC10WD BATTERY CHARGER DC10WD(1)	

Items of standard equipment and specifications may vary by country or area.



Makita Power Tools India Pvt. Ltd.

Unit II Sy. Nos. 93/3 & 93/4, Koralur Village, Kasaba Hobli,
Hoskote Taluk, Bengaluru - 560067
Email: info@makita.in Website: www.makita.in