



Satisfy Professional's Needs

LED Flashlight BML186 / BML146



Battery is sold separately.

LED

Long Continuous Bright illumination



Battery is sold separately.

Compact design for high portability

50 Hours Long continuous Bright illumination
ML186 with 18V Battery BL1830 (3.0Ah)

Overdischarge protection circuit



Push button type ON/OFF switch

Adjustable hand strap with hook & loop fastener

fits comfortably over any size hand to provide sure grip of the flashlight body.











Photo : BML146 with 14.4V Battery BL1415 (1.3Ah)

Battery is sold separately.

6 High-efficiency LEDs


Excellent vibration and impact resistance

500lx or more

	BML186 18V	BML146 14.4V	DC18RA	DC18SD	DC18SE (Automotive)
High Capacity 3.0Ah	 BL1830 (194204-5)	 BL1430 (194065-3)	 22 min. Fast Charging	 60 min.	 60 min.
Light weight 1.3Ah	 BL1815 (194513-2)	 BL1415 (194558-0)	 15 min. Fast Charging	 30 min.	 30 min.

LED Flashlight

BML186 / BML146



BML186

Continuous use (hours) 25^{*1} / 50^{*2}
Dimensions (L x W x H) 151 x 81 x 61^{*1} (78^{*2}) mm
(5-7/8" x 3-3/16" x 2-3/8"^{*1} (3-1/16"^{*2}))
Net weight^{*3} 0.54kg (1.18lbs)^{*1}



BML146

Continuous use (hours) 25^{*1} / 50^{*2}
Dimensions (L x W x H) 133 x 81 x 61^{*1} (78^{*2}) mm
(5-1/4" x 3-3/16" x 2-3/8"^{*1} (3-1/16"^{*2}))
Net weight^{*3} 0.48kg (1.05lbs)^{*1}



Standard Equipment : Battery and Charger are sold separately.

^{*1}with 1.3Ah battery ^{*2}with 3.0Ah battery ^{*3}weight according to EPTA-Procedure 01/2003
Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN BB-AD