



Petrol Chain Saw

EA6100P45E 380-600mm (15" - 24")

Stratified scavenging system complying with many exhaust emission regulations.



Features

- Low-vibration system with damper springs to absorb vibration from engine to integrated front and rear handles.
- Enhanced air filtration; centrifugal separation system effectively removes dust particles away from intake air and reduces dust stuck on the filter.
- Easy start-up with spring-assisted recoil starter reduces user's fatigue by drastic reduction of resistance caused when the starter rope is pulled.



Anti Vibration



Automatic Oiling



Capacitor Discharge Ignition



Primer Pump



Chain Brake



Rapid Start

Saw chain	Pitch : 0.325 or 3/8" Gauge: 1.5 mm (0.058")
Displacement	60.7 mL
Engine power	3.4 kW / 4.6 PS
Fuel Tank Capacity	0.8 L
Chain Oil Tank Volume	0.48 L
Sound Pressure Level	105 dB(A)
Sound Power Level	117 dB(A)
Vibration Level Front Grip	5.0 m/s ²
Vibration Level Rear Grip	4.0 m/s ²
Dimensions (L x W x H)	435x243x312 mm (17-1/8"x9-9/16"x12-1/4")
Power head weight	6.0 kg (13.2 lbs.)

Standard Accessories: Chain Blade, Guide Bar Cover, Wrenches



Makita Power Tools India Pvt. Ltd.

Unit II Sy. Nos. 93/3 & 93/4, Koralur village, Kasaba Hobli, Hoskote Taluk,
Bangalore - 560 067, INDIA. Tel: +91 80 2205 8200, Fax: +91 80 2854 9007
Email: sales@makita.in Website: www.makita.in