



Circular Saw

HS7010 185 mm (7-1/4") - 190 mm (7-1/2")



Powerful 1,600W motor delivers high power and performance

Steel plate base

One-finger switch

HS7010



photo : HS7010



One-finger trigger switch (HS7010 / HS7610)


Two-finger trigger switch



Rear dust exhaust port

Flat motor housing design increases stability when changing blades.

Angular guide at rear
For smooth and precise adjustment of bevel angle



Metal plate base (HS7010)

Aluminum plate base



Aluminum diecast safety cover

1,600W

Continuous rating input

Compatible with Guide rail (HS7610)

For use with Guide rail, the shape of base is designed to install Guide rail adapter.



Accessories/Optional

Guide rail adapter (Use with Guide rail)
Part No. 197005-0




Dust nozzle can be attached for use with a vacuum cleaner.

Part No. 196520-1



Guide rail



Overall length (m)	Part No.
1.4	194368-5
1.9	194925-9
3	194367-7

Circular Saw

HS7010 185 mm (7-1/4") - 190 mm (7-1/2")

HS7010

Continuous rating input	1,600W
Blade Diameter	185 / 190 mm (7-1/4" / 7-1/2")
Max Cutting Capacity	90°: 65 / 67 mm (2-9/16" / 2-5/8") 45°: 44 / 45 mm (1-3/4" / 1-3/4")
No Load Speed (RPM)	5,500
Dimensions (L x W x H)	300x240x261 mm (11-3/4"x9-1/2"x10-1/4")
Net weight	4.0 kg (8.9 lbs)
Power supply cord	2.5 m (8.2 ft)

Double Insulation

Dust Collection

Standard Equipment: Guide rule: 164095-8(1), Hex. wrench: 5 783217-7(1), TCT SAW: 185X40T D-81038(1)

The weight may differ depending on the attachment(s), including the battery cartridge.
The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.
Items of standard equipment and specifications may vary by country or area.



Makita Power Tools India Pvt. Ltd.

Unit II Sy. Nos. 93/3 & 93/4, Koralur Village, Kasaba Hobli,
Hoskote Taluk, Bengaluru - 560067
Email: info@makita.in Website: www.makita.in