

■ Various options



High Pressure Washer

HW1300 / HW1200

 Double Insulation	HW1300	HW1200
	Continuous rating input Max Pressure Max Flow Rate Max Feed Temperature High Pressure Hose Length Sound Pressure Level Vibration Level Dimensions (L x W x H) Net weight Power supply cord	1,800W 13 MPa (130 bar, 1,885 PSI) 450 L/h 40 °C (104 °F) 10 m (33 ft.) 76 dB(A) 4.86 m/s² 292x358x830mm (11-1/2"x14-1/8"x32-3/4") 12.7 kg (28.0 lbs.) 5.0m (16.4ft.)

Standard Equipment: HW1200: High pressure hose 10M:123784-4(1), Foam nozzle:1912Y2-5(1), Cyclone jet nozzle:197824-4(1), Trigger gun:197842-2(1), Variospray lance:197876-5(1)



High Pressure Washer
HW1300 / HW1200

Easy pressure adjustment and Self-Priming function



Simple function type
HW1200

High function type
2-pressure selection / Hose Reel
HW1300

Eco-friendly for reduced water



Makita Power Tools India Pvt. Ltd.
Unit II Sy. Nos. 93/3 & 93/4, Koralur Village, Kasaba Hobli,
Hoskote Taluk, Bengaluru - 560067
Email: info@makita.in Website: www.makita.in