



Compound Miter Saw


LS1221 305 mm (12")

Powerful 1,650W direct drive motor delivers 4,000 RPM for smooth performance




Compound Miter Saw



 Double Insulation

 Brake

 Bevel Cutting 45 Left

 Dust Collection

Continuous Rating Input	1,650W	153 mm
Blade Diameter	305 mm (12")	
Miter Angle	48 / 48° L 48, 48° R	
Bevel Angle	45° L	
Max Cutting Capacity (90°)	90°: 98 x 153 mm (3-7/8 x 6")	
Max Cutting Capacity (45°)	45°: 70 x 149 mm (2-3/4 x 5-7/8")	
No Load Speed (RPM)	4,000	
Dimensions (L x W x H)	674 x 610 x 607 mm (26-1/2 x 24 x 23-7/8")	
Blade Body Thickness	1.65 - 3.2 mm	
Hole Diameter	25.4, 30 mm (1, 1-3/16")	
Wheel Diameter	305 mm (12")	
Net weight	16.8 kg (37 lbs.)	
Power supply cord	2.5 m (8.2 ft)	

Standard Equipments: LS1221: Vise assembly: 122540-9(1), Dust bag assembly: 122852-0(1), Elbow: 416368-8(1), Triangular rule: 762001-3(1), Hex. wrench 6: 781044-6(1), TCT SAW BLADE 305MMX25.4X60T: B-03676(1), Holder 160: 323726-0(2)



Makita Power Tools India Pvt. Ltd.

Unit II Sy. Nos. 93/3 & 93/4, Koralur village, Kasaba Hobli, Hoskote Taluk,
Bangalore - 560067, INDIA. Tel: +91-80-2222-8200
Email: info@makita.in Website: www.makita.in