



Router


M3601B 6 mm, 8 mm, 1/4", 3/8"


Plunge depth adjustment lever with 3 pre-set depth stops for added precision




Router



 Double Insulation

 Dust Collection

Continuous rating input	900W	106 
Collet Capacity	6 mm, 8 mm or 1/4", 3/8"	
Plunge Capacity	0 - 35 mm (0 - 1-3/8")	
No Load Speed (RPM)	27,000	
Vibration Level	Cutting Grooves in MDF: 7.5 m/s ²	
Vibration K Factor	Cutting Grooves in MDF: 1.5 m/s ²	
Sound Pressure Level	91 dB(A)	
Sound Power Level	102 dB(A)	
Noise K Factor	3 dB(A)	
Dimensions (L x W x H)	256x110x218 mm (10-1/8"x4-5/16"x8-5/8")	
Net weight	2.7 kg (6.0 lbs.)	
Power supply cord	2.0 m (6.6 ft)	

Standard Equipment: Straight Guide, Straight Bit, Collet Cone, Wrench, Dust Nozzle (country-specific)



Makita Power Tools India Pvt. Ltd.

Unit II Sy. Nos. 93/3 & 93/4, Koralur village, Kasaba Hobli, Hoskote Taluk,
Bangalore - 560 067, INDIA. Tel: +91 80 2854 9008, Fax: +91 80 2854 9007
Email: sales@makita.in Website: www.makita.in