



Trimmer

M3700B 6 mm (1/4")

Top-mounted power cord stays out of the way for easier operation



Trimmer



Double Insulation

| | | |
|--------------------------------|---|-----|
| Continuous rating input | 530W | 411 |
| Collet Capacity | 6 mm or 1/4" | |
| No Load Speed (RPM) | 35,000 | |
| Plunge Capacity | 0 - 42 mm (0 - 1-5/8") | |
| Vibration Level | Rotation w/o Load: 2.5 m/s ² or less | |
| Vibration K Factor | Rotation w/o Load: 1.5 m/s ² | |
| Sound Pressure Level | 83 dB(A) | |
| Sound Power Level | 94 dB(A) | |
| Noise K Factor | 3 dB(A) | |
| Dimensions (L x W x H) | 82x90x199 mm (3-1/4"x3-1/2"x7-7/8") | |
| Net weight | 1.4 kg (3.1 lbs.) | |
| Power supply cord | 2.0 m (6.6 ft.) | |

Standard Equipment : Trimmer Guide, Straight Guide Assembly, Templet Guide, Straight Bit, Chip Deflector, Wrench x2



Makita Power Tools India Pvt. Ltd.

Unit II Sy. Nos. 93/3 & 93/4, Koralur village, Kasaba Hobli, Hoskote Taluk,
Bangalore - 560 067, INDIA. Tel: +91 80 2854 9008, Fax: +91 80 2854 9007
Email: sales@makita.in Website: www.makita.in