



High Speed Drill

M6501B 6.5 mm (1/4")

Variable speed trigger allows operator to adjust speed based on materials or application



High Speed Drill



-  Double Insulation
-  Variable Speed
-  Reversing

| | | |
|--------------------------------|--|---|
| Continuous rating input | 230W | 85  |
| Capacity | Steel: 6.5 mm (1/4") / Wood: 9 mm (11/32") | |
| No Load Speed (RPM) | 0 - 4,500 | |
| Vibration Level | Drilling into Metal: 3.0 m/s ² | |
| Vibration K Factor | Drilling into Metal: 1.5 m/s ² | |
| Sound Pressure Level | 70 dB(A) | |
| Noise K Factor | 3 dB(A) | |
| Dimensions (L x W x H) | 203x63x171 mm (8"x2-1/2"x6-3/4") | |
| Net weight | 0.95 kg (2.1 lbs.) | |
| Power supply cord | 2.0 m (6.6 ft.) | |

Standard Equipment: Chuck Key, Chuck Key Holder, Depth Gauge (country-specific), Cap (country-specific)



Makita Power Tools India Pvt. Ltd.

Unit II Sy. Nos. 93/3 & 93/4, Koralur village, Kasaba Hobli, Hoskote Taluk,
Bangalore - 560 067, INDIA. Tel: +91 80 2854 9008, Fax: +91 80 2854 9007
Email: sales@makita.in Website: www.makita.in