



M6600B

Mixer

Variable speed trigger allows operator to adjust speed based on materials or application



Powerful 800 W motor for improved mixing performance

165 mm (6-1/2") 800 W Variable Speed Mixer

Accessories / Optional

Shaft	Stainless steel (M12, L: 584mm, D: 12mm)		
Part No.	168349-5		

Mixing Blade dia(mm)	130	150	165
Shape			
Part No.	A-43670	A-43686	A-43692

Bolt Size (Bolt sold separate)	M8 x 18	-	M8 x 18
Part No.	265220-5	-	265220-5

Shaft	Stainless steel (M12, L: 584mm, D: 12mm)	
Shape		
Part No.	168349-5	A-43773

Shaft	Stainless steel (M12, L: 584mm, D: 12mm)		
Part No.	A-43773		

Mixing Blade dia(mm)	135	175	175
Shape			
Part No.	A-43723	A-43701	136865-5

Mixing Blade dia(mm)	183	190	201
Shape			
Part No.	A-43739	A-33065	A-33071

Mixing Blade dia(mm)	220	
Shape		
Part No.	A-43717	

Mixer M6600B



Specification :	
Continuous rating input	800W
Blade Diameter	165 mm (6-1/2")
No Load Speed (RPM)	0 - 700
Vibration Level	2.5 m/s ² or less
Vibration K Factor	1.5 m/s ²
Sound Pressure Level	85 dB(A)
Sound Power Level	96 dB(A)
Noise K Factor	3 dB(A)
Dimensions (L x W x H)	280x86x388 mm (11"x3-3/8"x15-1/4")
Net weight	2.6 - 2.7 kg (5.7 - 5.9 lbs.)
Power supply cord	2.0 m (6.6 ft.)

- Double Insulation
- Variable Speed

Standard Equipment :

M6600B : Grip 36 complete: 142088-5(1), Wrench 19: 781010-3(1)