



Rotary Hammer

M8700B 22 mm (7/8"), Adapted for SDS-PLUS bits

Improved bit guide for increased bit stability during drilling applications



Rotary Hammer



- Double Insulation
- Variable Speed
- Reversing
- SDS-PLUS Shank
- Torque Limiter
- Carrying Case

Standard Equipment : Side Grip, Depth Gauge

Continuous rating input Capacity	710W Concrete: 22 mm (7/8") Core Bit: 54 mm (2-1/8") Diamond Core Bit (Dry Type): 65 mm (2-9/16") Steel: 13 mm (1/2") Wood: 32 mm (1-1/4")	459
Blows Per Minute (BPM)	0 - 4,350	
No Load Speed (RPM)	0 - 1,100	
Vibration Level	Hammer Drilling into Concrete: 16.5 m/s ²	
Sound Pressure Level	90 dB(A)	
Sound Power Level	101 dB(A)	
Noise K Factor	3 dB(A)	
Dimensions (L x W x H)	362x71x194 mm (14-1/4"x2-13/16"x7-5/8")	
Net weight	2.5 - 2.9 kg (5.6 - 6.4 lbs.)	
Power supply cord	4.0 m (13.1 ft.)	



Makita Power Tools India Pvt. Ltd.

Unit II Sy. Nos. 93/3 & 93/4, Koralur village, Kasaba Hobli, Hoskote Taluk,
Bangalore - 560 067, INDIA. Tel: +91 80 2854 9008, Fax: +91 80 2854 9007
Email: sales@makita.in Website: www.makita.in