



Cordless Chain Saw
DUC204 / DUC254 / DUC254C
200 mm (8") 250 mm (10") 250 mm (10")



Lightweight & High SpeedChain

Efficiency equivalent to 23mL classengine chain saw



Photo: DUC254



Optional Accessories

Guide Bar / Saw Chain / Guide Bar Cover
Cutter type: MC: Micro chisel, CC:Chamfer chisel

Guide Bar				Saw Chain						Bar Cover	Drive sprocket	
Bar length	Motor Mount	Type	Part No.	No.of drive links	gauge	pitch	Type OREGON/ DOLMAR	Cutter type	Part No.	Part No.	Type	Part No.
25cm/10"	---	Solid carving bar	168407-7	60	1.3mm/ .050"	1/4"	25AP/ 466	MC	194098-8	452093-7	Sprocket	198259-2
20cm/8"	A041	Sprocket nose bar	161848-6	33	1.1mm/ .043"	3/8"LP	90PX/ 291	CC	199076-3	458503-2	Sprocket	199063-2
25cm/10"	A041	Sprocket nose bar	161846-0	40					199075-5	452093-7		
25cm/10"	A041	Sprocket nose bar	168408-5	40					196205-9	452093-7		

File and File holder
For Model :Chain saw *with gurip

Sawchain type	Size	File	File and Fileholder
		Part No.	Part No.
25AP, 91PX, 91VLX, 466, 492, 196	4mm	*744003-1	---
		D953003090	195089-2 D953030010
90PX, 33SL, 34SL, 291	4.5mm	D953003100	195923-6 D953030020

File handle, Flat file & Depth gauge jointer
For all saw chain

File handle	Flatfile	Depth gauge jointer
Part No.	Part No.	Part No.
D953004010	D953003060	D953100090

Chain oil		BIOTOPChain oil	
Size	Part No.	Size	Part No.
100mL	182229-1	1L	D980008610
1L	195093-1 D988002656	5L	D980008611
5L	D988002658		

Spike bumper	
Part No.	
199067-4	

Cordless Chain Saw		DUC204 200 mm / DUC254 , DUC254C 250 mm (10")					
	Variable Speed	DUC204		DUC254		DUC254C	
		GuideBar Length	200mm (8")	250mm (10")	250mm (10") (Carving Bar)		
	Brake	Chain Pitch / Chain Gauge	3/8" / 1.1 mm (0.043")	3/8" / 1.1 mm (0.043")	3/8" / 1.3 mm (0.050")	1/4" / 1.3 mm (0.050")	
		Chain Speed	0 -24 m/s(0- 1,440m/min) (0- 4,720FPM)	0 -24 m/s(0- 1,440m/min) (0- 4,720FPM)	0 -22.5 m/s(0- 1,350m/min) (0- 4,430FPM)		
	Soft Start	Chain Oil Tank Volume	140 mL	140 mL	140 mL		
		Sound Pressure Level	92.2 dB(A)	92.2 dB(A)	92.2 dB(A)		
	Automatic Oiling	Sound Power Level	103.2 dB(A)	103.2 dB(A)	103.2 dB(A)		
		Vibration Level	Cutting Wood: 3.1 m/s²	Cutting Wood: 3.1 m/s²	Cutting Wood: 4.1 m/s²		
	Chain Brake	Dimensions(L x Wx H)	w/o GuideBar : 258x184x191mm (10-1/8"x7-1/4"x7-1/2") w/ 20 cm (7-7/8") 90PXSprocket NoseBar: 417x184x191mm (16-3/8"x7-1/4"x7-1/2")	w/o GuideBar : 258x184x191mm (10-1/8"x7-1/4"x7-1/2") w/ 25 cm (10") 90PXSprocket NoseBar: 482x184x191mm (19"x7-1/4"x7-1/2")	w/o GuideBar : 258x184x191mm (10-1/8"x7-1/4"x7-1/2") w/ 25 cm (10") 25APCarving Bar : 496x184x191mm (17-1/2"x7-1/2"x7-1/4")		
		Net weight	2.8 - 3.1kg (6.2 -6.8 lbs.)	2.8 - 3.2kg (6.2 -6.9 lbs.)	2.9 - 3.3kg (6.3 -7.3 lbs.)		
Standard Equipment:							
DUC254Z: Guide bar 10: 61846-0(1), Saw chain 10: 191H00-0(1), Guide bar case: 458501-6(1)							
DUC254HZ:Saw chain 10: 191D60-8(1), Guide bar case: 458501-6(1)							