



Angle Grinder

GA4050R 100 mm (4")

Enhanced shaft locking mechanism; Gear housing is redesigned to minimize breakage of the shaft locking mechanism; Large size lock pin cap allows for normal shaft locking operation even with a thick-gloved finger



Angle Grinder



Double Insulation



Dust Collection



Anti-restart function



Soft Start

Continuous rating input 1,200 W (110 V)

260 mm

Amperage 11.5 A (110 V)

Wheel diameter 100 mm (4")

No load speed 11,600 min⁻¹

Vibration Level 2.5 m/s²

Uncertainty (K) 3 dB(A)

Sound Pressure Level 94 dB(A)

Sound Power Level 102 dB(A)

Dimensions (L x W x H) 325 x 117 x 100 mm

Net weight 2.3 - 2.6 kg

Power supply cord 2.5 m (8.2 ft)

Standard Equipment : Grip 36 complete 158237-4(1), Lock nut wrench 20 782420-7(1)



Makita Power Tools India Pvt. Ltd.

Unit II Sy. Nos. 93/3 & 93/4, Koralur village, Kasaba Hobli, Hoskote Taluk,
Bangalore - 560 067, INDIA. Tel: +91 80 2854 9008, Fax: +91 80 2854 9007
Email: sales@makita.in Website: www.makita.in