

















The tool body is separated into the upper and lower housings which joined with vibration absorbing cushion rubbers to reduce load on battery and terminal.








Smooth cutting with vertical crank system

**Tool-less shoe adjustment** 

Easy blade ejection lever







## **High Cutting Speed**



## ø25.4mm (1") Carbon steel pipe

JR001G	110
18Vx2 Predecessor Model	100
Slow	



SPF 2 x 10					
	JR001G		135		
	18Vx2 Predecessor Model	100			
	Slow			Fast	

## Lightweight

**4.2**kg
Battery: BL4025

Work amount on a full battery charge\*1
Battery: BL4040

about **130** pcs ø25.4mm (1") Carbon steel pipe about 155 pcs

Length of Stroke	32 mm (1-1/4")
Strokes Per Minute (SPM)	High / Low: 0 - 3,000 / 0 - 2,300
Capacity	Pipe: 130 mm (5-1/8") / Wood: 255 mm (10")
Sound Pressure Level	85 dB(A)
Sound Power Level	96 dB(A)
Dimensions (L x W x H)	w/ BL4025: 457x88x233 mm (18"x3-1/2"x9-1/8")
	w/ BL4040: 472x88x239 mm (18-5/8"x3-1/2"x9-3/8")
Net weight	4.2 - 4.5 kg (9.3 - 9.9 lbs.)

<sup>\*1</sup> The test results depend to a great extent on the test material etc.