



**Cordless Slide Compound Miter Saw**  
**LS004G 260 mm (10-1/4")**

■ Max. cutting capacity (height x width)

Model	Cross Cut	Miter Cut (left & right)	Bevel Cut (left & right)	Compound Cut	Crown molding, 45 degree type	Baseboard
LS003G	92 x 382 mm (3-5/8" x 15")	Miter 45° left / right	Bevel 45° left	Bevel 45° left / right	Upright cutting 203 mm (8")	Upright cutting 171 mm (6-3/4")
		LS003G: 92 x 268 mm (3-5/8" x 10-1/2") LS004G: 68 x 218 mm (2-11/16 x 8-5/8)	LS003G: 61 x 382 mm (2-3/8" x 15") LS004G: 42 x 310 mm (1-5/8 x 12-1/4)	LS003G: 61 x 268 mm (2-3/8" x 10-1/2") LS004G: 42 x 218 mm (1-5/8 x 8-5/8)	LS003G: Upright cutting 203 mm (8") LS004G: Upright cutting 168 mm (6-5/8)	LS003G: Upright cutting 171 mm (6-3/4") LS004G: Upright cutting 133 mm (5-1/4")
LS004G	68 x 310 mm (2-11/16 x 12-1/4)	Miter 60° left / right	Bevel 45° right	Bevel 45° right / Miter 45° left / right	Horizontal cutting 320 mm (12-5/8")	Horizontal cutting (Skirt board) 416 mm (16-3/8")
		LS003G: 92 x 185 mm (3-5/8" x 7-1/4") LS004G: 68 x 155 mm (2-11/16 x 6-1/8)	LS003G: 44 x 382 mm (1-3/4" x 15") LS004G: 29 x 305 mm (1-1/8 x 12)	LS003G: 44 x 268 mm (1-3/4" x 10-1/2") LS004G: 29 x 215 mm (1-1/8 x 8-1/2)	LS003G: Horizontal cutting 320 mm (12-5/8") LS004G: Horizontal cutting 248 mm (9-3/4")	LS003G: Horizontal cutting (Skirt board) 416 mm (16-3/8") LS004G: Horizontal cutting 305 mm (12")

■ Optional Accessories

Specialized EFFICUTblade  
Part No. B-67256  
Size (mm)  
305 x 30 x 60T



Sub base assembly set  
Part No. 191U61-8  
LS004G only



Horizontal vise assembly  
Part No. 122470-4



Vertical vise assembly  
Part No. 126617-2



Part No. B-64624  
Size (mm)  
260 x 45T

Crown molding stopper set  
Part No. 192628-9



Stand  
Part No. WST06 / WST07



Part No. WST05



Dust bag assembly  
Part No. 122852-0



Charging Time Reference

	DC40RA Fast Charging	DC40RC
BL4020 2.0Ah	22min	30min
BL4025 2.5Ah	28min	38min
BL4040 4.0Ah	45min	67min
BL4050F 5.0Ah	50min	85min

Cordless Slide Compound Miter Saw		
LS003G / LS004G 305 mm (12") / 260 mm (10-1/4")		
	Brake	LS003G: 305 mm (12") LS004G: 260 mm (10-1/4")
	Constant Speed	60° L / 60° R 48° L / 48° R
	Soft Start	90° Miter: 92 x 382 mm (3-5/8 x 15"), 107 x 363 mm (4-1/4 x 14-1/4") 45° Miter/L/R: 92 x 268 mm (3-5/8 x 10-1/2"), 107 x 255 mm (4-1/4 x 10")
	Soft Start	90° Miter: 68 x 310 mm (2-11/16 x 12-1/4"), 91 x 279 mm (3-5/8 x 11") 45° Miter/L/R: 68 x 218 mm (2-11/16 x 8-5/8"), 91 x 197 mm (3-5/8 x 7-3/4")
	Led Marker	No Load Speed (RPM) 3,600 Sound Pressure Level 91 dB(A) Sound Power Level 100 dB(A)
	Dust Collection	Dimensions (L x W x H) 898 x 690 x 725 mm (35-1/4 x 27-1/4 x 28-1/2") Net weight 30.5 - 31.1 kg (67.2 - 68.6 lbs.)
	Built-in Job Light	805 x 644 x 660 mm (31-3/4 x 25-3/8 x 26") 26.6 - 27.2 kg (58.6 - 60.0 lbs.)

Standard Equipment : LS004GZ: Dust bag assembly: 122852-0(1), Vise assembly: 126617-2(1), Triangular rule: 762001-3(1), Hex. wrench 6: 781044-6(1)



LED lamp to cast an exact cutting line



LS003G  
305 mm (12")



LS004G  
260 mm (10-1/4")

Max. cutting capacity (height x width)	
LS003G 92 x 382 mm	LS004G 68 x 310 mm