



Cordless Circular Saw HS011G 260 mm (10-1/4") / 270 mm (10-5/8")



XGT
40V Li-ion
max



Lightweight
with BL4050F

6.1 kg

Max cutting depth
with 270mm sawblade

101 mm

Work amount

on a single full battery charge

Melapi (Thickness:90mm /
Width: 1,000mm / Bevel angle: 0°)
with BL4050F

40 cuts



High power and lightweight design

BL
MOTOR

Rotatable dust nozzle

Sub base
Sub base can be used as
Guiderule by turning up
side down.

Magnesium diecast
Baseplate, Safety cover
and Blade case

Compatible with guide rail without adapter
providing precision cutting

Twin LED Job light
with pre-glow and after
glow functions



Bevel cuts up to 1° left
and 60° right.



Constant speed control
minimizes reduction in rotation speed
under load, keeping operation efficiency.

XPT eXtreme Protection
Technology

(BRAKE) Electric brake

AWS Auto-start Wireless
System

The wireless activation function enables clean and comfortable operation. By connecting a supported tool to the cleaner, you can run the cleaner automatically along with the switch operation of the tool.

Wireless unit is compatible with all supported tools


Accessories/Optional

Specialized EFFICUT blade




Size (mm)	Part No.
260 x 2.15 x 25 x 24T	E-07733
270 x 2.15 x 25.4 x 24T	E-12974

Guide rail



Overall length (m)	Part No.
1	199140-0
1.4	194368-5
1.5	199141-8
1.9	194925-9
3	194367-7

Clamp set



Part No. type A: 194385-5
type B: 199826-6

Bevel guide set

Adjustable angle of
Guide rail



Part No. 196664-7


Guide rail bag



For 1.0m Guide rail
Part No. E-05670

For 1.4m, 1.5m
Guide rail
Part No. E-05664

Guide rail Joint
connector 2pc set



Part No. 198884-9
198885-7(EU)

Charging Time

	Fast Charging	
	DC40RA	DC40RC
BL4020 2.0Ah	22 min	30 min
BL4025 2.5Ah	28 min	38 min
BL4040 4.0Ah	45 min	67 min
*1 BL4050F5.0Ah	50 min	85 min
*1 BL4080F8.0Ah	76 min	170 min

*1 Recommended battery

Cordless Circular Saw

HS011G 260 mm (10-1/4") / 270 mm (10-5/8")

Brake	Hole Diameter	15.88, 25, 25.4, 30 mm (5/8, 1")
Constant Speed	Max Cutting Capacity	0°: 97 - 101 mm (3-13/16 - 4") 45°: 68 - 71 mm (2-11/16 - 2-13/16") 60°: 48 - 51 mm (1-7/8 - 2")
Soft Start	No Load Speed (RPM)	3,500
Dust Collection	Vibration Level	2.5 m/s ² or less
Built-in Job Light	Sound Pressure Level	93 dB(A)
Anti - Restart Function	Sound Power Level	104 dB(A)
	Dimensions (L x W x H)	w/ BL4020/ BL4025/ BL4040/ BL4050 For w/o Battery: 453 x 196 x 336 mm (17-7/8 x 7-3/4 x 13-1/4") w/ BL4080F: 453 x 214 x 336 mm (17-7/8 x 8-3/8 x 13-1/4")
	Net weight	5.5 - 6.7 kg (12.1 - 14.8 lbs.)

Standard Equipment :

HS011GZ: Sub base : 162A32-2(1), Hex wrench: 6 783204-6(1), EFFICUT FOR WOOD CUTTING/ GENE: E-07733(1)

HS011GT201: Sub base : 162A32-2(1), Hex wrench: 6 783204-6(1), EFFICUT FOR WOOD CUTTING/ GENE: E-07733(1), Battery BL4050F: 1918A8-1(2), DC40RA FAST CHARGER DC40RA(1)

Items of standard equipment and specifications may vary by country or area.