



DHG181 Cordless Heat Gun

Max 550°C air temperature



Photo : DHG181

Max. Air Flow
200 L/min

For various applications



Continuous run time
At max air temperature 550°C, Air Flow: 200L/min (DHG181, Stage 2)
about **21 min** Battery: BL1860B
(on a full battery charge)



Quick release mechanism for easy Nozzle replacement
Nozzle can be removed without touching the hot metal part simply by turning Plasticring.
Compatible with current nozzles for AC machines



Air volume setting (DHG181 only)
The air volume is switchable by sliding the air volume switch to:
Stage 1: 120 L/min, Stage 2: 200 L/min



Single LED job light with after-glow function



Lock-off lever
Trigger switch



Lock-on button

Hanging hook



Air temperature adjustment dial (DHG181 only)
Stepless adjustment for setting to suitable temperature for your application



Photo : DHG181



Optional Accessories

Glass protection nozzle

Part No.
PR00000028



Wide-slot nozzle

Part No.
PR00000029



Reflector nozzle

Part No.
PR00000030



Reduction nozzle 20

Part No.
PR00000031



Overlap welding nozzle

Part No.
PR00000032



Solder sleeves reflector

Part No.
PR00000033



Welding nozzle

Part No.
PR00000034



Pressureroller

Part No.
PR00000035



Scraper

Part No.
PR00000040



Scraper set

Part No.
PR00000041

Scraper
Part No.
PR00000042



Charging Time

	Fast Charging		
	DC18RC	DC18RD	DC18SD
BL1815N 1.5Ah	15 min		30 min
BL1820B 2.0Ah	24 min		45 min
BL1830B 3.0Ah	22 min		60 min
BL1840B 4.0Ah	36 min		90 min
BL1850B 5.0Ah	45 min		110 min
BL1860B 6.0Ah	55 min		130 min

Cordless Heat Gun

DHG181 / DHG180

- Electronic 2-Speed (DHG181 only)
- Built-in Job Light
- Carrying Case

Standard Equipment :

DHG181RT:
Battery BL1850B: 198013-4(1),
GLASS PROTECTION NOZZLE: PR00000028(1),
WIDE-SLOT NOZZLE: PR00000029(1),
REFLECTOR NOZZLE: PR00000030(1),
REDUCTION NOZZLE: 20mm PR00000031(1),
PLASTIC CASE: PR00000040(1),
DC18RC FAST CHARGER DC18RC(1)

DHG181ZK:
GLASS PROTECTION NOZZLE: PR00000028(1),
WIDE-SLOT NOZZLE: PR00000029(1),
REFLECTOR NOZZLE: PR00000030(1),
REDUCTION NOZZLE: 20mm PR00000031(1),
PLASTIC CASE: PR00000040(1)

DHG181	
Air Temperature	Dial 1/ 2/3/ 4/5/ 6: Ambient temperature/150/ 250/ 350/ 450/ 550°C
Air Flow	Stage1: 120 L/min, Stage2: 200 L/min
Dimensions (L x W x H)	w/ BL1815N/ BL1820B: 173 x 79 x 237mm (6-3/16 x 3-1/8 x 9-3/8") w/ BL1830B/ BL1840B/ BL1850B/ BL1860B: 173 x 79 x 255mm (6-3/16 x 3-1/8 x 10")
Net weight	1.0 - 1.4kg (2.2 - 3.1 lbs.)

DHG180	
Air Temperature	550°C
Air Flow	200 L/min
Dimensions (L x W x H)	w/ BL1815N/ BL1820B: 168 x 79 x 234mm (6-5/8 x 3-1/8 x 9-1/4") w/ BL1830B/ BL1840B/ BL1850B/ BL1860B: 168 x 79 x 251mm (6-5/8 x 3-1/8 x 9-7/8")
Net weight	1.0 - 1.3kg (2.2 - 2.9 lbs.)



Makita Power Tools India Pvt. Ltd.

Unit II Sy. Nos. 93/3 & 93/4, Koralar Village, Kasaba Hobli,
Hoskote Taluk, Bengaluru - 560067
Email: info@makita.in Website: www.makita.in