




Stroke		
Length	Per Minute	
<b>22</b> mm	<b>0 - 3,100</b> spm	









Wide hook (Tool hanger) Part No. 197224-8





## Charging Time

18V UITHUMHON	DC18RC	DC18SD
<b>BL1815N</b> 1.5Ah	15 min	30 min
<b>BL1820B</b> 2.0Ah	24 <sub>min</sub>	45 min
<b>BL1830B</b> 3.0Ah	22 min	60 min
<b>BL1840B</b> 4.0Ah	36 min	90 min
<b>BL1850B</b> 5.0Ah	45 min	110 min
<b>BL1860B</b> 6.0Ah	55 min	130 min

## **Cordless Recipro Saw**

## **DJR189**

Variable Speed

( Brake Constant Speed

**≣**○ Built-in Job Light Carrying Case

Sound Pressure Level Sound Power Level Vibration Level

Capacity

Net weight

Dimensions (L x W x H)

Strokes per minute (SPM) 0 - 3.100 Wood: 255 mm (10"), Pipe: 130 mm (5-1/8") 88 dB(A) 99 dB(A) Cutting boards: 9.0 m/s<sup>2</sup> Cutting wooden beams: 8.7 m/s² w/BL1815N/BL1820B: 393 x 81 x 179 mm (15-1/2 x 3-3/16 x 7", w/BL1830B/BL1840B/BL1850B/BL1860B: 410 x 81 x 182 mm 2.2 - 2.5 kg (4.9 - 5.5 lbs.)

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.

Items of standard equipment and specifications may vary by country or area.

Standard Equipment: Recipro saw blades, Battery, Charger

## Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan