



Battery Powered Pruning Shears DUP180

LXT



Max cutting
capacity
Ø30mm

about
8,000
pcs*

Lightweight
0.68 kg
Tool only

Battery
adapter
type



*When cutting Ø15mm branches of Japanese cypress, with BL1860B battery

18V
LITHIUM-ION

BL **XPT**
MOTOR



Cordless Pruning Saw

DUC150

18V

BL XPT



Battery Powered Pruning Shears

DUP362

18V x2

XPT



Cordless Earth Auger

DDG461

18V x2

BL ADT XPT



DCU180

18V

BL XPT



DCU601

18V x2

BL XPT



DCU602

18V x2

BL XPT



DCU603

18V x2

BL XPT WG



DCU604

18V x2

BL XPT WG



DCU605

18V x2

BL WG



Accessories

Shear blade U set

Replacement upper blade for Pruning shears



Shear blade L set

Replacement lower blade for Pruning shears



Dresser stone set

Dresser stone for Shear blade sharpening



Holster

Storage and carrying of the machine



MAKPAC TYPE3

For smart organization and easy transportation of power tools and accessories



Charging Time

	Fast Charging	
	DC18RC	DC18SD
BL1815N 1.5Ah	15 min	30 min
BL1820B 2.0Ah	24 min	45 min
BL1830B 3.0Ah	22 min	60 min
BL1840B 4.0Ah	36 min	90 min
BL1850B 5.0Ah	45 min	110 min
BL1860B 6.0Ah	55 min	130 min

Battery Powered Pruning Shears

DUP180

- Brake
- Anti-restart function
- Torque Limiter
- Carrying Case

Capacity	Max cutting: 30 mm (1-3/16")
Vibration level	2.5 m/s ² or less
Sound pressure level	70 dB(A) or less
Dimensions* (L x W x H)	296 x 40 x 99 mm (11-5/8 x 1-9/16 x 3-7/8")
Net weight*	0.68 kg (1.5 lbs.)

*Without standard equipment such as battery, battery adapter, harness, and controller for operation

Standard Equipment :

DUP180Z - Oil vessel 182470-6(1); Dressing stone set 1912E4-1(1); Box wrench 13 782212-4(1); Hex. wrench 4 783202-0(1); Hex. wrench 2.5 783208-8(1)

The weight according to EPTA-Procedure 01/2014 is shown in the table.
Items of standard equipment and specifications may vary by country or area.



Makita Power Tools India Pvt. Ltd.

Unit II Sy. Nos. 93/3 & 93/4, Koralur Village, Kasaba Hobli,
Hoskote Taluk, Bengaluru - 560067
Email: info@makita.in Website: www.makita.in