

Shear Wrench series

6924N
M22 (7/8") / M24 (1") / SHTB22
1,100 N·m
AC



6922NB
M16 (5/8") / M20 (3/4") / M22 (7/8")
804 N·m
AC



DWT310
M16 (5/8") / M20 (3/4") / M22 (7/8")
804 N·m
18V x2



Impact Wrench series

TW001G
3/4" (19 mm)
1,800 N·m
40V max



TW007G
TW008G
1/2" (12.7 mm)
760 N·m
40V max



TW004G
TW005G
1/2" (12.7 mm)
350 N·m
40V max



DTW1001
3/4" (19 mm)
1,050 N·m



DTW700
DTW701
1/2" (12.7 mm)
700 N·m
18V



DTW300
DTW301
1/2" (12.7 mm)
330 N·m
18V



Accessories

Sleeve size reference table

* Type F (for HEXA TECH (GFD France))
** for Chinese market



Bolt Size	Outer sleeve			Inner sleeve		Bolt Size	Outer sleeve			Inner sleeve	
	Hex (mm)	L (mm)	Part No.	L (mm)	Part No.		Hex (mm)	L (mm)	Part No.	L (mm)	Part No.
M16	27	35	764362-7	36	764416-0	M22, 7/8"	36	39	153909-6	39	764418-6
		81	764367-7	82	*764421-7			39	*764423-3		
		100	764406-3	100	764400-5			85	764364-3	85	764352-0
		200	764407-1	200	764401-3			100	764410-2	100	764404-7
		37	764361-9	38	764417-8			170	764365-1	170	764354-6
M20	32	37	**196276-6	38	764417-8	200	764411-0	200	764405-5		
		37	764361-9	38	*764422-5	35	764362-7	36	764420-9		
		83	764363-5	84	764357-0	37	764361-9	38	764419-4		
		100	764408-9	100	764402-1	83	764363-5	84	764353-8		
		200	764409-7	200	764403-9	168	764366-9	169	764355-4		
5/8"	1-1/16"					3/4"	1-1/4"				

Charging Time

Battery	Fast Charging	
	DC40RA	DC40RC
*1 BL4020 2.0Ah	22 min	30 min
*1 BL4025 2.5Ah	28 min	38 min
*1 BL4040/F 4.0Ah	45 min	67 min
*1 BL4050/F 5.0Ah	50 min	85 min

*1 Recommended battery

Cordless Shear Wrench	
WT001G M16 (5/8"), M20 (3/4"), M22 (7/8")	
Brake	Capacity High strength torque shear bolt (HTB): M16, M20, M22 (5/8, 3/4, 7/8") Super (high) strength torque shear bolt (SHTB): M16, M20 (5/8, 3/4")
Anti-restart function	No load speed 17 min ⁻¹
Carrying Case	Max fastening torque 804 N·m (593 ft.lbs.) Sound pressure level 82 dB (A) Sound power level 90 dB (A) Vibration level 2.5 m/s ² or less
	Dimensions w/ M22 Sleeve, w/ BL4020, BL4025: 255 x 95 x 334 mm (10 x 3-3/4 x 13-1/8") w/ M22 Sleeve, w/ BL4050F: 289 x 95 x 360 mm (11-3/8 x 3-3/4 x 14-1/8")
	Net weight 5.2 - 5.9 kg (11.5 - 13.0 lbs.)

Standard Equipment : - Screwdriver, Shoulder belt, Outer sleeve, Inner sleeve, Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202310



Lightweight

5.5 kg

battery: BL4040
* Without Sleeve

Lightweight design



Reduces the stress on user's body in such a tough application as upward tightening of nut under steel beam.


Higher maneuverability

Max. Torque shear bolt capacity
M22

- High strength torque shear bolt (HTB): **M16, M20, M22**
- Super high strength torque shear bolt (SHTB): **M16, M20**
- A325 Torque shear bolt: **5/8, 3/4, 7/8"**
- A490 Torque shear bolt: **5/8, 3/4"**



Battery capacity warning lamp



BL
MOTOR

High power with BL motor

WT001G

5.5 kg

battery: BL4040



Predecessor Model

7.1 kg

battery: BL1860Bx2

* Without Sleeve

Large work amount

Fastening capacity of M22 Torque shear bolt:

battery: BL4025

Approx. 150 pcs

battery: BL4040

Approx. 250 pcs

Hook designed for use with shoulder belt to carry the tool

Shoulder belt (for transportation)



Hook



Bolt-tip ejection lever

enables easy ejection of removed bolt-tip left in the socket of the machine.



XPT

eXtreme Protection Technology

