



Pneumatic Finish Nailer AF635

Pneumatic Finish Nailer powered by pressure air 0.49 - 0.83 MPa.

Anti-dry-fire mechanism
to prevent workpiece from damage

Ergonomically designed rubber grip
with anti-slipping Rib provides more comfort and better control

Air duster
By pushing the push button, air from compressor can be bypassed into the air duster nozzle to produce powerful air blast for sweeping up job site floor as well as workpiece.



Protective bumpers
protect work piece and body from scratches or damage

Hook

Remaining nail view window

Tool-less nail jam clearing

Easy-to see slim nose tip
allows quick and easy access to a desired fastening point.

Tool-less Driving depth adjustment simply by turning a dial.

Pneumatic Finish Nailer AF635

-  Depth Adjusting
-  Carrying Case
-  Sequential or Bump-fire

Capacity	Length: 32 - 64 mm (1-1/4" - 2-1/2") Gauge: 15 Ga
Operating Pressure	0.49 - 0.83 MPa (70 - 120 PSI)
Magazine Capacity	100
Dimensions (L x W x H)	339x100x309mm (13-3/8"x3-15/16"x12-1/8")
Net weight	1.8 kg (4.0 lbs)

Standard Equipment :

Safety Goggles, Oil supply, Nose Adapter

weight according to EPTA-Procedure 01/ver.2.1

Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 201608

