



Battery Powered Backpack Blower UB004C Portable Power Pack PDC1500



Max blowing force

Boost mode*

28 N

With Standard nozzle / PDC1500

Max air volume

Boost mode*

20.9 m³/min

Run time

Blowing force of 10N / Max blowing force

200 / 55 min

With Standard nozzle / PDC1500 / Cruise control lever

*Max continuous use of Boost mode is 10 sec. After 10 sec. of use, the machine does not shift to Boost mode for 20 sec.

With End nozzle 74



With Flat nozzle



Accessories

End nozzle 74 set

Part No. 1914H0-2

A nozzle suitable for blowing away wet fallen leaves or other heavy objects.



Flat nozzle set

Part No. 1914H1-0

A nozzle for blowing off fallen leaves adhering to the ground, etc.



Portable Power Pack

Portable Power Pack

High energy capacity of 1,500Wh PDC1500

Charger
DC4001

Charging time
PDC1500: 450 min.



Energy capacity of 1,200Wh PDC1200

Charger
DC4001

Charging time
PDC1200: 360 min.



XPT

High water-resistance allows to operate the machine even if it is wet with water.

Battery Powered

Blower
UB003C



Grass Trimmer

UR101C
UR201C
UR202C



Backpack Blower
UB004C



Lawn mower
LM001C



Adapter set

40Vmax

Part No.
191N62-4



Adapter between Battery box of Portable power pack and Product on 40Vmax XGT platform

18Vx2

Part No.
191J51-5



Adapter between Battery box of Portable power pack and Product on 18Vx2 LXT platform

Charging Time

	DC4001
	450 min
	360 min

Battery Powered Backpack Blower

UB004C

	Variable Speed	Air volume	w/ PDC1500, Cruise control mode, Mode 1 / 2 / 3: 8.5 / 15.2 / 19.7 m ³ /min w/ PDC1500, Boost mode: 20.9 m ³ /min
	Anti-restart function	Max air velocity	w/ PDC1500, Cruise control mode, Mode 1 / 2 / 3: 33.2 / 59.0 / 76.3 m/s w/ PDC1500, Boost mode: 80.7 m/s
	Electronic 3-Speed	Blowing force	w/ PDC1500, Cruise control mode, Mode 1 / 2 / 3: 5 / 15 / 25 N w/ PDC1500, Boost mode: 28 N
	Constant Speed	No load speed	Cruise control mode, Mode 1 / 2 / 3: 10,500 / 18,000 / 22,500 min ⁻¹ Boost mode: 23,800 min ⁻¹
		Continuous use (Attachment) (Battery)	55-200 min Standard nozzle PDC1500
		Vibration level	Operation w/o load, EN50636-2-100: 2.5 m/s ² or less
		Vibration K factor	Operation w/o load, EN50636-2-100: 1.5 m/s ²
		Sound pressure level	EN50636-2-100: 82.3 dB(A)
		Sound power level	EN50636-2-100: 96.1 dB(A)
		Noise K factor	3.1, 2.1 dB(A)
		Dimensions (L x W x H)	460 x 575 x 585 mm (18-1/8 x 22-5/8 x 23")
		Net weight	16.5 - 18.6 kg (36.4 - 41.0 lbs.)
		(Battery)	PDC1200 - PDC1500

Standard Equipment :

End nozzle, Flat nozzle, Pipe support belt complete, Pipe belt complete

Portable Power Pack

PDC1500

Capacity	43.55 Ah
Energy capacity	1,567.8 Wh
Number of cells	130
Charging time	450 min.
Dimensions (L x W x H)	w/o Harness: 369 x 312 x 131 mm (14-1/2 x 12-1/4 x 5-1/8")
Net weight	Battery only: 10.9 kg (24.0 lbs.)* Harness assembly: 12.9 kg (28.4 lbs.)*
Power supply cord	Battery side: 1.2 m (3.9 ft) Adapter side: 0.6 m (2.0 ft)

*not covered by EPTA-Procedure

Standard Equipment : Harness, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.

Items of standard equipment and specifications may vary by country or area.



Makita Power Tools India Pvt. Ltd.

Unit II Sy. Nos. 93/3 & 93/4, Koralur Village, Kasaba Hobli,

Hoskote Taluk, Bengaluru - 560067

Email: info@makita.in Website: www.makita.in