



Cordless Breaker
HM004G

Satisfy Professional's Needs



28.6mm Hex
Shank Type

40V^{Li-ion}_{max} + 40V^{Li-ion}_{max}



XGT X2
80V_{max}

High power similar to corded models

Impact energy

72.8 Joule

Low Vibration

6.5 m/s²

BL
MOTOR

AVT

AWS

SOFT
NO LOAD

XPT

XGT X2
80Vmax



40Vmax + 40Vmax

Powered by two 40Vmax XGT Li-Ion batteries in series (80Vmax)

BL MOTOR

High power brushless motor

Impact energy
72.8 Joule



AWS

(Auto-start Wireless System)

Connects to compatible vacuum cleaner with Bluetooth. The vacuum cleaner automatically runs while the switch is on.

Bluetooth



Accessories

Dust extractor attachment set

w/o hose

Part No. 197168-2

** 197170-5

w/ hose

Part No. 197148-8

** 197172-1

**With Sensomatic chip



Charging Time

		Fast Charging			
		DC40RA	DC40RB	DC40RC	DC40WA
BL4020	2.0Ah	22 min		30 min	110 min
BL4025	2.5Ah	28 min		38 min	130 min
*1 BL4040/F	4.0Ah	45 min		67 min	210 min
*1 BL4050F	5.0Ah	50 min		85 min	260 min
*1 BL4080F	8.0Ah	76 min		170 min	420 min

*1 Recommended battery

Low Vibration thanks to

AVT

(Anti-Vibration Technology)


Vibration level

6.5 m/s²

Active dynamic vibration absorber moves in the opposite direction to the drive piston to reduce vibration.

Vibration absorbing housing



provides a practical combination of high power and low vibration.



Vibration absorbing spring (4 places)

Counter weight mechanism

reduces vibration during chipping operation.




Counterweight

Piston

SOFT NO LOAD

Suppression of motor speed during no-load



During no-load



Under load



Slim body for excellent visibility

219mm



Hex shank: 28.6mm

Self sharpening bull point (Country-specific)

XPT

(eXtreme Protection Technology)



Main power switch

Battery capacity warning lamp



Maintenance warning lamp

LED job light

Twin LEDs with preglow and afterglow functions



Cordless Breaker

HM004G 1-1/8" : 28.6mm Hex Shank

28.6mm Hex Shank

Constant Speed

Soft Start

Built-in Job Light

Anti-restart function

Impact energy	72.8 J (53.7 ft.lbs.)
Blows per minute (BPM)	870
Shank diameter	28.6 mm (1-1/8")
Sound power level	103 dB(A) (Uncertainty (K): 1.62 dB(A))
Sound pressure level	95 dB(A) (Uncertainty (K): 1.62 dB(A))
Vibration level	6.5 m/s ² (Uncertainty (K): 1.5 m/s ²)
Dimensions (L x W x H)	882 x 227 x 540 mm (34-3/4 x 8-15/16 x 21-1/4")
Net weight	29.7 - 32.1 kg (65.5 - 70.8 lbs.)

Standard Equipment : Hex wrench, Bull point, Wireless unit set

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita

Unit II Sy. Nos. 93/3 & 93/4, Korlur village, Kasaba Hobli, Hoskote Taluk, Bengaluru - 560 067.
Email: info@makita.in | Website: www.makita.in