



Cordless Breaker HM004G

XGT



28.6mm Hex
Shank Type

40V^{Li-ion} max + 40V^{Li-ion} max



XGT X2
80V^{max}

High power similar to corded models



Impact energy

72.8 Joule

Low Vibration

6.5 m/s²

BL MOTOR **AVT** **AWS** **SOFT NO LOAD** **XPT**

XGT X2
80Vmax

40V^{Li-ion} + 40V^{Li-ion}

BL
MOTOR

High power
brushless
motor

Impact energy

72.8 Joule

AWS

(Auto-start Wireless System)

Connects to compatible vacuum cleaner with Bluetooth.
The vacuum cleaner automatically runs while the switch is on.

Bluetooth®



Accessories

Dust extractor attachment set

w/o hose
Part No. 197168-2
** 197170-5

w/ hose
Part No. 197148-8
** 197172-1

**With Sensomatic chip



Charging Time

	Fast Charging	DC40RA	DC40RB	DC40RC	DC40WA
BL4020 2.0Ah		22 min		30 min	110 min
BL4025 2.5Ah		28 min		38 min	130 min
*BL4040/F 4.0Ah		45 min		67 min	210 min
*BL4050/F 5.0Ah		50 min		85 min	260 min
*BL4080/F 8.0Ah		76 min		170 min	420 min

*1 Recommended battery

**Powered by two 40Vmax XGT
Li-ion batteries in series
(80Vmax)**

Low Vibration
thanks to **AVT**
(Anti-Vibration Technology)


Vibration level **6.5 m/s²**

Active dynamic vibration absorber moves in the opposite direction to the drive piston to reduce vibration.

Vibration absorbing housing

provides a practical combination of high power and low vibration.

Vibration absorbing spring
(4 places)



**Slim body
for excellent
visibility**




— Hex shank: 28.6mm

— Self sharpening
bull point
(Country-specific)

Counter weight mechanism

reduces
vibration
during
chipping
operation.



SOFT NO LOAD

Suppression of motor speed
during no-load



XPT

(eXtreme Protection Technology)



Main power switch



LED job light

Twin LEDs with preglow and afterglow functions



Cordless Breaker

HM004GZ01

	28.6mm Hex Shank
	Constant Speed
	Soft Start
	Built-in Job Light
	Anti-restart function

Impact energy 72.8 J (53.7 ft.lbs.)

Blows per minute (BPM) 870

Shank diameter 28.6 mm (1-1/8")

Sound power level 103 dB(A) (Uncertainty (K): 1.62 dB(A))

Sound pressure level 95 dB(A) (Uncertainty (K): 1.62 dB(A))

Vibration level 6.5 m/s² (Uncertainty (K): 1.5 m/s²)

Dimensions (L x W x H) 882 x 227 x 540 mm
(34-3/4 x 8-15/16 x 21-1/4")

Net weight 29.7 - 32.1 kg (65.5 - 70.8 lbs.)

Standard Equipment: HM004GZ01 - Wireless unit set 199393-1(1); Hex. wrench 5 783203-8(1); 28.6MM HEX SELF SHARPENING B-10372(1)



Makita Power Tools India Pvt. Ltd.

Unit II Sy. Nos. 93/3 & 93/4, Koralur Village, Kasaba Hobli,

Hoskote Taluk, Bengaluru - 560067

Email: info@makita.in Website: www.makita.in