



Cordless Trimmer DRT52 6 / - mm (- / 1/4")

Satisfy Professional's Needs

LXT



Work amount

Cut Melapi (1m) with a ø6mm straight
bit and at a cutting depth of 6mm

about 105 m

Battery: BL1860B
on a full battery charge

18V
LITHIUM-ION

BL **XPT**
MOTOR

Brushless motor provides output efficiency similar or superior to that of our corded models.



**BL
MOTOR**



Lock/unlock button and Power button

Lock/unlock button
LED lamp for indication of being unlocked
Power button



Smooth and precision depth adjustment

with rack and pinion mechanism



Rubberized soft grip

provides comfort and control



Transparent plastic base

for clear view of trimming edge



XPT

(eXtreme Protection Technology)

Accessories

Trimmer base assembly set

Transparent base

Part No. 194267-1* Part No. 194268-9



Standard equipment



*With Fine depth adjustment

Tilt base for chamfering

Part No. 194269-7* Part No. 194270-2



*With Fine depth adjustment

Charging Time

	Fast Charging DC18RC	DC18SD
BL1815N 1.5Ah	15 min	30 min
BL1820B 2.0Ah	24 min	45 min
BL1830B 3.0Ah	22 min	60 min
BL1840B 4.0Ah	36 min	90 min
BL1850B 5.0Ah	45 min	110 min
BL1860B 6.0Ah	55 min	130 min

Cordless Trimmer

DRT52 6 mm (1/4")



Soft Start



Anti-restart function

Collet size	6 mm (1/4")
No load speed	30,000 min ⁻¹
Base shape	Square (82 x 90mm)
Vibration level	Rotation w/o load: 2.5 m/s ² or less
Net weight	1.3 - 1.6 kg (2.9 - 3.5 lbs.)
Net weight (Battery)	BL1815N - BL1860B

Standard Equipment :

DRT52Z - Trimmer guide assembly 122703-7(1); Straight guide assembly 122704-5(1); Straight bit 6 set 191Y83-2(1); Templet guide 10 343577-5(1); Chip deflector 418647-0(1); Wrench 10 781036-5(1); Wrench 17 781037-3(1)

DRT52SF - Trimmer guide assembly 122703-7(1); Straight guide assembly 122704-5(1); Straight bit 6 set 191Y83-2(1); Battery BL1830B set 197605-6(1); Templet guide 10 343577-5(1); Chip deflector 418647-0(1); Wrench 10 781036-5(1); Wrench 17 781037-3(1); Plastic case 821798-4(1); DC18SD BATTERY CHARGER DC18SD(1)

DRT52F002 - Trimmer guide assembly 122703-7(1); Straight guide assembly 122704-5(1); PLASTIC CASE COMPLETE 141389-6(1); Straight bit 6 set 191Y83-2(1); Battery BL1830B set 197605-6(1); Templet guide 10 343577-5(1); Chip deflector 418647-0(1); Wrench 10 781036-5(1); Wrench 17 781037-3(1); DC18WC BATTERY CHARGER DC18WC(1)

The weight may differ depending on the attachment(s), including the battery cartridge.

The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.

Items of standard equipment and specifications may vary by country or area.



Makita Power Tools India Pvt. Ltd.

Unit II Sy. Nos. 93/3 & 93/4, Koralur Village, Kasaba Hobli,

Hoskote Taluk, Bengaluru - 560067

Email: info@makita.in Website: www.makita.in