



# Cordless Heat Gun DHG181 / DHG180

## Max 550°C air temperature



Photo : DHG181

Max. Air Flow  
**200 L/min**

For various applications



### Continuous run time

At max air temperature 550°C, Air Flow: 200L/min (DHG181, Stage 2)

about **21 min** Battery: BL1860B  
(on a full battery charge)



**Quick release mechanism for easy Nozzle replacement**

Nozzle can be removed without touching the hot metal part simply by turning Plastic ring. Compatible with current nozzles for AC machines



**Air volume setting (DHG181 only)**

The air volume is switchable by sliding the air volume switch to:  
Stage 1: 120 L/min, Stage 2: 200 L/min



**Single LED job light with after-glow function**



Lock-off lever  
Trigger switch

Lock-on button

**Hanging hook**



**Air temperature adjustment dial (DHG181 only)**

Stepless adjustment for setting to suitable temperature for your application



Photo : DHG181



**Wide Variety of Accessories**

**Glass protection nozzle**

Part No. PR00000028



**Wide-slot nozzle**

Part No. PR00000029



**Reflector nozzle**

Part No. PR00000030



**Reduction nozzle 20**

Part No. PR00000031



**Overlap welding nozzle**

Part No. PR00000032



**Solder sleeves reflector**

Part No. PR00000033



**Welding nozzle**

Part No. PR00000034



**Pressure roller**

Part No. PR00000035



**Scraper**

Part No. PR00000040



**Scraper set**

Part No. PR00000041



**Scraper**

Part No. PR00000042

**Charging Time**

Battery Model	Fast Charging	
	DC18RC	DC18RD
BL1815N 1.5Ah	15 min	30 min
BL1820B 2.0Ah	24 min	45 min
BL1830B 3.0Ah	22 min	60 min
BL1840B 4.0Ah	36 min	90 min
BL1850B 5.0Ah	45 min	110 min
BL1860B 6.0Ah	55 min	130 min

**Cordless Heat Gun**

**DHG181 / DHG180**

- Electronic 2-Speed (DHG181 only)
- Built-in Job Light
- Carrying Case

**Standard Equipment :**

Glass protection nozzle, Wide slot nozzle, Reflector nozzle, Reduction nozzle, Battery, Charger

DHG181	
Air Temperature	Dial 1/2/3/4/5/6; Ambient temperature/150/250/350/450/550°C
Air Flow	Stage 1: 120 L/min, Stage 2: 200 L/min
Dimensions (L x W x H)	w/ BL1815N / BL1820B: 173 x 79 x 237 mm (6-3/16 x 3-1/8 x 9-3/8") w/ BL1830B / BL1840B / BL1850B / BL1860B: 173 x 79 x 255 mm (6-3/16 x 3-1/8 x 10")
Net weight	1.0 - 1.4 kg (2.2 - 3.1 lbs.)
DHG180	
Air Temperature	550°C
Air Flow	200 L/min
Dimensions (L x W x H)	w/ BL1815N / BL1820B: 168 x 79 x 234 mm (6-5/8 x 3-1/8 x 9-1/4") w/ BL1830B / BL1840B / BL1850B / BL1860B: 168 x 79 x 251 mm (6-5/8 x 3-1/8 x 9-7/8")
Net weight	1.0 - 1.3 kg (2.2 - 2.9 lbs.)

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.



**Makita Power Tools India Pvt. Ltd.**

Unit II Sy. Nos. 93/3 & 93/4, Koralur village, Kasaba Hobli, Hoskote Taluk, Bangalore - 560 067 | Tel: +91-80-2205-8200  
Email: info@makita.in Website: www.makita.in