



Cordless Blower UB002G

Satisfy Professional's Needs



Compact and lightweight, easy to maneuver

Max air volume

3.6 m³/min

Battery: BL4040F / without nozzle

Max air velocity

99 m/s

Battery: BL4040F / with standard nozzle

Max air velocity

76 m/s

Battery: BL4040F / with garden nozzle



With the standard nozzle

With the garden nozzle

Continuous use

Blower

High / Med. / Low:

20 / 60 / 120 min

Vacuum

19 min

Battery: BL4025 on a full battery charge



For cleaning around job sites



For blowing in grooves



For clearing pathways

With the standard nozzle | Overall length **515 mm**



ø40mm air outlet diameter

With the garden nozzle | Overall length **859 mm**



The garden nozzle is an optional accessory depending on the country.

The air volume has been enhanced by enlarging the suction inlet.



3-stage air volume settings by dial with variable speed control by trigger



Vacuum function
Vacuuming is available with the dust bag*



*The dust bag is an optional accessory depending on the country.

Accessories

Long nozzle assembly

Part No. 123246-2



Garden nozzle assembly set

Part No. 191G09-6



Flexible hose set

Part No. 191M34-3



Flexible hose set

Part No. 196643-5



Dust bag assembly

Part No. 123241-2



Brush nozzle set

Part No. 191M30-1



Wiper nozzle set

Part No. 191M32-7



Tapered nozzle set

Part No. 192236-6



Charging Time

	Fast Charging DC40RA	DC40RC
*1 BL4020 2.0Ah	22 min	30 min
*1 BL4025 2.5Ah	28 min	38 min
*1 BL4040/F 4.0Ah	45 min	67 min
BL4050F 5.0Ah	50 min	85 min
BL4080F 8.0Ah	76 min	170 min

*1 Recommended battery

Cordless Blower

UB002G

- Variable Speed
- Electronic 3-Speed

Standard Equipment :
Nozzle assembly,
Garden nozzle assembly,
Dust bag, Battery,
Charger

*2 EN 62841-1

Blowing force	Standard nozzle: 3.1 - 3.2 N / Garden nozzle: 3.0 - 3.1 N
Max air volume	Blower: 3.5 - 3.6 m ³ /min / Vacuum: 2.0 m ³ /min
Max air velocity	Standard nozzle: 98 - 99 m/s / Garden nozzle: 75 - 76 m/s
Max sealed suction	5.4 kPa
Continuous use (Battery)	Blower, High / Med. / Low: 20 / 60 / 120 min. / Vacuum: 19 min. BL4025
Vibration level*2	Standard nozzle, operation without load (blowing / vacuuming): 2.5 m/s ² or less
Vibration K Factor*2	Standard nozzle, operation without load (blowing): 1.5 m/s ²
Sound pressure level*2	Standard nozzle, operation without load (blowing): 84 dB(A) / (vacuuming): 87 dB(A)
Sound power level*2	Standard nozzle, operation without load (blowing): 92 dB(A) / (vacuuming): 95 dB(A)
Noise K factor*2	Standard nozzle, operation without load (blowing / vacuuming): 3 dB(A)
Dimensions (L x W x H) (Battery)	515 x 156 x 227 mm (20-1/4 x 6-1/8 x 8-15/16") BL4025
(Attachment)	Standard nozzle
Net weight (Battery)	2.0 - 3.5 kg (4.4 - 7.7 lbs.) BL4020 - BL4080F

The weight may differ depending on the attachment(s), including the battery cartridge. Items of standard equipment and specifications may vary by country or area.



Makita Power Tools India Pvt. Ltd.

Unit II Sy. Nos. 93/3 & 93/4, Koralur village, Kasaba Hobli, Hoskote Taluk, Bengaluru - 560067.
Email: info@makita.in

Website: www.makita.in