



Cordless Blower UB002G

Satisfy Professional's Needs



XGT
40V^{Li-ion}max

Compact and lightweight, easy to maneuver

Max air volume

3.6 m³/min

Battery: BL4040F / without nozzle

Max air velocity

99 m/s

Battery: BL4040F / with standard nozzle

Max air velocity

76 m/s

Battery: BL4040F / with garden nozzle



With the standard nozzle



With the garden nozzle

Continuous use

Blower

High / Med. / Low:

20 / 60 / 120 min

Vacuum

19 min

Battery: BL4025 on a full battery charge



XGT

40V^{Li-ion}max



For cleaning around
job sites



For blowing in grooves



For clearing pathways

With the standard nozzle | Overall length
515 mm



ø40mm air outlet
diameter

With the garden nozzle | Overall length
859 mm



The garden nozzle is an optional accessory
depending on the country.

The air volume has been
enhanced by enlarging
the suction inlet.



3-stage air volume settings
by dial with variable speed
control by trigger



Vacuum function
Vacuuming is available with
the dust bag*



XPT
eXtreme Protection
Technology

*The dust bag is an optional
accessory depending on the country.

Accessories / Optional

Long nozzle assembly

Part No. 123246-2



Garden nozzle assembly set

Part No. 191G09-6



Flexible hose set

Part No. 191M34-3



Flexible hose set

Part No. 196643-5



Dust bag assembly

Part No. 123241-2



Brush nozzle set

Part No. 191M30-1



Wiper nozzle set

Part No. 191M32-7



Tapered nozzle set

Part No. 192236-6



Charging Time

	Fast Charging DC40RA	DC40RC
40V^{Li-ion}max		
*1 BL4020 2.0Ah	22 min	30 min
*1 BL4025 2.5Ah	28 min	38 min
*1 BL4040/F 4.0Ah	45 min	67 min
BL4050F 5.0Ah	50 min	85 min
BL4080F 8.0Ah	76 min	170 min

*1 Recommended battery

Cordless Blower

UB002G

Variable Speed	Blowing force Max air volume Max air velocity Max sealed suction Continuous use (Battery)	Standard nozzle: 3.1 - 3.2 N / Garden nozzle: 3.0 - 3.1 N Blower: 3.5 - 3.6 m ³ /min / Vacuum: 2.0 m ³ /min Standard nozzle: 98 - 99 m/s / Garden nozzle: 75 - 76 m/s 5.4 kPa Blower, High / Med. / Low: 20 / 60 / 120 min. / Vacuum: 19 min. BL4025
Electronic 3-Speed	Vibration level*2 Vibration K Factor*2 Sound pressure level*2 Sound power level*2 Noise K factor*2 Dimensions (L x W x H) (Attachment) Net weight (Battery)	Standard nozzle, operation without load (blowing / vacuuming): 2.5 m/s ² or less Standard nozzle, operation without load (blowing): 1.5 m/s ² Standard nozzle, operation without load (blowing): 84 dB(A) / (vacuuming): 87 dB(A) Standard nozzle, operation without load (blowing): 92 dB(A) / (vacuuming): 95 dB(A) Standard nozzle, operation without load (blowing / vacuuming): 3 dB(A) 515 x 156 x 227 mm (20-1/4 x 6-1/8 x 8-15/16") BL4025 Standard nozzle 2.0 - 3.5 kg (4.4 - 7.7 lbs.) BL4020 - BL4080F

Standard Equipment : UB002GZ:Nozzle assembly-123245-4(1)



Makita Power Tools India Pvt. Ltd.
Unit II, Sy. Nos. 93/3 & 93/4, Koralur Village, Kasaba Hobli,
Hoskote Taluk, Bengaluru - 560067

Email: info@makita.in

Website: www.makita.in