



Cordless Hedge Trimmer

UH020G 500mm (19-3/4")
UH021G 600mm (23-5/8")

Satisfy Professional's Needs



40V Li-ion max



Lightweight and compact enough to handle easily,
yet capable of high power trimming



Runtime*
UH020G/UH021G

110 / 105 min

Battery: BL4040

Strokes per minute

4,200 min⁻¹

Net weight
UH020G/UH021G

3.0 / 3.1 kg

Battery: BL4020

*Continuous run time (approx) on a single full battery charge (under no-load)



High efficiency, High durability, High power

Smooth and efficient trimming

- The output power and number of strokes have been increased compared with our 18V models, achieving smooth and efficient trimming.
- Constant speed control suppresses rotation drop to enable stable trimming.



Blade type

Single-sided blade with obliquely-angled and triple-ground teeth



With excellent branch introduction and a design that prevents branches from escaping, the blades smoothly capture branches, allowing for trimming without letting branches escape.



Photo: UH020G

UH020G Blade length: 500mm
UH021G Blade length: 600mm

Lightweight design

The guide bar is made of aluminum to make the front of the tool lighter for reducing user fatigue.

Highly durable crank mechanism

- Increased crank wall thickness can:
- reduce the chance of falling off of the blade from the crank.
- increase the contact area with the blade, reducing wear of the crank.




Chip receiver (option)


- smoothly takes in branches and leaves
- Smooth shape for excellent collection



- Leaves and branches are less likely to fall and slip



Less likely to fall



Less likely to slip


Redesigned, easy-to-press switch lever

can be pressed without gripping the front handle deep in your palm, allowing for easy control.



Reverse function to clear jams

When the shear blades are jammed with branches, the shear blades are reversed for a moment to clear the jam by pressing the Reverse button and then pulling the trigger.



LED

Reverse button to clear jams

Optional Accessories

Model No.	Shear blade set	Blade cover	Chip receiver
UH020G(500mm)	1914G4-7	413L91-8	1910T1-0
UH021G(600mm)	1914G5-5	413L92-6	1910T2-8

Grease vessel set
199450-5



XPT / IPX4
-compatible

High water-resistance allows the user to operate the tool even if it is wet with water.

Charging Time

	Fast Charging DC40RA	DC40RC
*1 BL4020 2.0Ah	22 min	30 min
*1 BL4025 2.5Ah	28 min	38 min
*1 BL4040/F 4.0Ah	45 min	67 min
BL4050F 5.0Ah	50 min	85 min
BL4080F 8.0Ah	76 min	170 min

*1 Recommended battery

Cordless Hedge Trimmer

UH020G 500mm (19-3/4") UH021G 600mm (23-5/8")

	UH020G	UH021G
Brake	500mm (19-3/4")	600mm (23-5/8")
Constant Speed	30.0mm (1-3/16")	30.0mm (1-3/16")
Grass Tangle Removing Function	20.0mm (13/16")	20.0mm (13/16")
Anti-restart function	Strokes Per Minute 4,200min ⁻¹	4,200min ⁻¹
	Continuous use w/BL4040: 110 min	w/BL4040: 105 min
	Sound pressure level* 83 dB(A)	83 dB(A)
	Noise K factor* 3 dB(A)	3 dB(A)
	Measured sound power level* 91.0 dB(A)	91.0 dB(A)
	Guaranteed sound power level* 93 dB(A)	93 dB(A)
	Vibration level* 2.5 m/s ² or less	2.5 m/s ² or less
	Vibration K factor* 1.5 m/s ²	1.5 m/s ²
	Dimensions (L x W x H) w/BL4040: 929 x 207 x 185 mm (36-1/2 x 8-1/8 x 7-1/4")	w/BL4040: 1,048 x 207 x 185 mm (41-1/4 x 8-1/8 x 7-1/4")
	Net weight** 3.0 - 4.2kg (6.6 - 9.3 lbs.)	3.1 - 4.3kg (6.8 - 9.5 lbs.)
	Net weight (Battery) BL4020 - BL4080F	BL4020 - BL4080F

Standard Equipment :

UH020GZ: Blade cover 500: 413L91-8(1)

UH020GD101: Battery BL4025: 191B41-0(1), Blade cover 500: 413L91-8(1), FAST CHARGER DC40RA(1)