



## Cordless Impact Wrench TW011G

Satisfy Professional's Needs



**XGT**  
**40V<sup>Li-ion</sup>max**

# High power and long anvil with 19mm (3/4") square drive

Max fastening torque

**1,500\*** N·m

The maximum fastening torque  
at 6 seconds after seating

Nut-busting torque

**1,900\*\*** N·m

at max impact mode (4)

\*When tightening an M30 friction grip bolt

\*\*The maximum torque value at which an M33 friction grip bolt can be loosened within 3 seconds.



**XGT**  
**40V<sup>Li-ion</sup>max**

## Suitable for loosening and tightening bolts and nuts in recessed areas



### Electronic 4-stage impact power selection

enables user to control the  
power and speed depending on  
the applications.

Mode	No load speed (min <sup>-1</sup> )	Impacts per minutes (min <sup>-1</sup> )
1. Soft	0-500	-
2. Med.	0-700	0-1,400
3. Hard	0-1,100	0-2,000
4. Max.	0-1,800	0-2,600

**Full speed mode**  
Allows the tool to  
reach full speed with  
fewer trigger pull,  
minimizing fatigue  
during continuous  
work.

### Accessories

#### Extension handle set

Part No. 191G67-2



### Charging Time

	Fast Charging DC40RA	DC40RC
*1 BL4020 2.0Ah	22 min	30 min
*1 BL4025 2.5Ah	28 min	38 min
*1 BL4040/F 4.0Ah	45 min	67 min
BL4050F 5.0Ah	50 min	85 min
BL4080F 8.0Ah	76 min	170 min

\*1 Recommended battery

### Mode settings suitable for removing and installing tires, etc.

Mode	Behavior of the tool (Work example)	Target fastening torque	Reverse
1. Soft	Stops immediately after seating (Manual tightening of large truck tires) with Auto-stop	30 - 50 N·m*	Rotates slowly after finishing impacts, with Auto-stop
2. Med.	Stops approx. 0.3 seconds after seating (Initial tightening of large truck tires) with Auto-stop	50 - 150 N·m*	
3. Hard	Stops approx. 0.5 seconds after seating (Temporary tightening of large truck tires) with Auto-stop	300 - 450 N·m*	
4. Max.	Tightens at the maximum speed	1,500 N·m**	Loosens at the maximum speed

\*With M20 - M24 bolts    \*\*At 6 seconds after seating, with an M30 friction grip bolt

Cordless Impact Wrench	TW011G
Variable Speed	Square drive 19.0 mm (3/4") Max fastening torque 6-sec tightening: 1,500 N·m (1,110 ft.lbs.) 3-sec tightening: 1,250 N·m (922 ft.lbs.)
Brake	Nut-busting torque (Other conditions) 1,900 N·m (1,400 ft.lbs.) The maximum torque value at which an M33 friction grip bolt can be loosened within 3 seconds.
Reversing	No load speed Max / Hard / Med. / Soft: 0 - 1,800 / 0 - 1,100 / 0 - 700 / 0 - 500 min <sup>-1</sup>
Electronic 4-Speed	Impacts per minute (Other conditions) Max / Hard / Med. / Soft: 0 - 2,600 / 0 - 2,000 / 0 - 1,400 / - min <sup>-1</sup> In Soft mode (Mode 1), the tool stops as soon as an impact is detected.
Constant Speed	Vibration level / Vibration K factor* Impact tightening of fasteners of the maximum capacity of the tool: 15.6 m/s <sup>2</sup> / 2.4 m/s <sup>2</sup>
Built-in Job Light	Sound pressure level* 104 dB(A)
Carrying Case	Sound power level* 112 dB(A)
	Noise K factor* 3 dB(A)
	Dimensions (L x W x H) (Battery) 329 x 94 x 297 mm (13 x 3-11/16 x 11-3/4")
	Net weight (Battery) 4.3 - 5.5 kg (9.5 - 12.1 lbs.)
	BL4025 BL4020 - BL4080F

Standard Equipment : Hook, Battery, Charger, Tool bag

\*EN62841-2-2



**Makita Power Tools India Pvt. Ltd.**  
Unit II Sy. Nos. 93/3 & 93/4, Korlur village, Kasaba Hobli, Hoskote Taluk,  
Bengaluru - 560 067.  
Email: info@makita.in | Website: www.makita.in