



Cordless Impact Driver DTD201

Satisfy Professional's Needs

LXT

High-speed, high-power for heavy-duty tasks



Max fastening torque

210 N·m

High-speed rotation

Max
3,700 min⁻¹

BL MOTOR **XPT**

Enhanced hammer and spring with increased motor speed deliver superior fastening performance to our previous model.

Work efficiency*

DTD201

160

Our 18V model **100**

*Drove coach screws (lag screws) with a length of 90mm and a diameter of 9.0mm into melapi.



4-stage impact power selection + T-mode (for thin metal sheets only)

Four selectable speed settings make it easy to adjust the tool for a wide range of applications.



4-stages
4 (Max)
3 (Hard)
2 (Medium)
1 (Soft)

T-mode

XPT
eXtreme Protection
Technology



One-touch bit installation

Reduced resistance allows for easier bit installation.



Anti-bit wobbling structure

Ensures enhanced stability during fastening.

LED job light

Twin LEDs with preglow and afterglow functions



Variable speed control by trigger

Allows for speed adjustments based on the material or application.

Soft grip

Ergonomic rubberized soft grip for increased comfort



Reversing
switch

Hook

Charging Time

	Fast Charging DC18RC	DC18SD
*BL1815N 1.5Ah	15 min	30 min
*BL1820B 2.0Ah	24 min	45 min
*BL1830B 3.0Ah	22 min	60 min
*BL1840B 4.0Ah	36 min	90 min
*BL1850B 5.0Ah	45 min	110 min
*BL1860B 6.0Ah	55 min	130 min
BL1890 9.0Ah	85 min	200 min
BL18120 12.0Ah	120 min	265 min
	LXT BASIC Compatible with charger DCB18WA only	DCB18WA
BLB182 2.0Ah		90 min

*1 Recommended battery

Accessories / Optional

Tool hanger set
Part No. 191K57-9

Hook set
Part No. 194654-4

Battery protector set
Part No. 194649-7

Cordless Impact Driver	DTD201
Variable Speed	Capacity Steel: 22 mm (7/8") / Wood (Auger bit): 24 mm (15/16")
Brake	Max fastening torque 210 N·m (1,860 in.lbs.)
Reversing	No load speed Max / Hard / Med. / Soft: 0 - 3,700 / 0 - 3,200 / 0 - 2,100 / 0 - 1,100 min ⁻¹
Electronic 4-Speed	Impacts per minute Max / Hard / Med. / Soft: 0 - 4,400 / 0 - 4,200 / 0 - 3,600 / 0 - 2,000 min ⁻¹
Built-in Job Light	Vibration level 9.9 m/s ² (EN62841-2-2, Mode: impact tightening with max. capacity)
Carrying Case	Vibration K factor 1.5 m/s ² (EN62841-2-2, Mode: impact tightening with max. capacity)
	Sound pressure level 97 dB (A) (EN62841-2-2)
	Sound power level 105 dB (A) (EN62841-2-2)
	Noise K factor 3 dB (A) (EN62841-2-2)
	Dimensions (L x W x H) 121 x 81 x 246 mm (4-3/4 x 3-3/16 x 9-11/16")
	(Battery) BL1860B
	Net weight 1.3 - 2.3 kg (2.9 - 5.1 lbs.)
	(Battery) BL1815N - BL18120
Standard Equipment :	
DTD201Z - Hook 346317-0(1)	
DTD201RTJ - Hook 346317-0(1), Connector plastic case (type 2) 821550-0(1), Inner tray 837670-0(1), Battery BL1850B 198013-4(2), DC18RC FAST CHARGER DC18RC(1)	

The net weight value includes the lightest and heaviest combination of the attachment(s) for normal and safe use and battery cartridge(s) which are specified in the instruction manual.
Items of standard equipment and specifications may vary by country or area.



Makita Power Tools India Pvt. Ltd.
Unit II, Sy. Nos. 93/3 & 93/4, Koralur Village, Kasaba Hobli,
Hoskote Taluk, Bengaluru - 560067
Email: info@makita.in | Website: www.makita.in