



Cordless Framing Nailer BN001G / BN002G

Satisfy Professional's Needs



XGT
40V **Li-ion**
max



Excellent rapid-fire performance
with a pneumatic feel

Rapid firing capability

about **4** shots per second

BN001G

Clipped-head



Nail capacity

Length
50-90 mm
Gauge
2.9-3.3 mm
Collation angle display
30-34°



BN002G

Round-head



Nail capacity

Length
50-90 mm
Gauge
2.9-3.8 mm
Collation angle display
21°



XGT
40V **Li-ion**
max

Offers superior rapid-fire capability
with a similar feel to a pneumatic nailer



photo: BN002G



photo: BN002G

Main power switch

LED job light

- Single LED
- With preglow and afterglow functions



Driving depth adjustment

Adjustable with the dial



Anti-dry fire mechanism

Activated before the number of remaining nails reaches zero, avoiding missed shots.

Operation mode

Selectable from Full sequential actuation mode (for single nailing) / Contact actuation mode (for continuous nailing)



BL **XPT**
MOTOR

photo: BN001G



Window for checking remaining nail quantity



Anti-slip nose

Redesigned tip shape ensures stability and efficiency during angled nailing.



Hooks

Equipped with a belt hook and a 38mm rafter hook for easy hanging on ladders, scaffolding, and timbers.



Accessories / Optional

- Nose Adapter Set
- Extended Capacity Magazine Set



BN001G:
Part No. 1917P3-0
Maximum magazine
capacity: 97 nails



BN002G:
Part No. 1914P9-0
Maximum magazine
capacity: 78 nails

Charging Time

	Fast Charging	DC40RA	DC40RC
*1 BL4020 2.0Ah		22 min	30 min
*1 BL4025 2.5Ah		28 min	38 min
*1 BL4040/F 4.0Ah		45 min	67 min
BL4050F 5.0Ah		50 min	85 min
BL4080F/H 8.0Ah		76 min	170 min

*1 Recommended battery

Cordless Framing Nailer

BN001G / BN002G

	BN001G	BN002G
Anti-restart function	Nail capacity	Nail capacity
Depth Adjustment	Length: 50 - 90mm (2 - 3-1/2")	Length: 50 - 90 mm (2 - 3-1/2")
Sequential and Bump-fire	Gauge: 2.9 - 3.3mm (0.113 - 0.131")	Gauge: 2.9 - 3.8mm (0.113 - 0.148")
Auto Firing Stop	Collation angle display: 30 - 34°	Collation angle display: 21°
Built-in Job Light	Max magazine capacity 58 nails	Max magazine capacity 41 nails
Carrying Case	Work volume on a full battery charge (Battery)	Work volume on a full battery charge (Battery)
	1,020 (BL4025)	4 (BL4025)
	Rapid firing capability per second (Battery)	Rapid firing capability per second (Battery)
	4 (BL4025)	3.7 m/s ² (EN60745-2-16)
	Vibration level	1.5 m/s ² (EN60745-2-16)
	Uncertainty (K) for Vibration	90 dB (A) (EN60745-2-16)
	Sound pressure level	101 dB (A) (EN60745-2-16)
	Sound power level	3 dB (A) (EN60745-2-16)
	Uncertainty (K) for Noise	Dimensions (L x W x H)
	326 x 186 x 358 mm (12-7/8 x 7-3/8 x 14-1/8")	389 x 189 x 358 mm (15-1/4 x 7-7/16 x 14-1/8")
	BL4025	BL4025
	Net weight	5.3 - 6.5 kg (11.7 - 14.3 lbs.)
	(Battery)	5.4 - 6.6 kg (11.9 - 14.6 lbs.)
	BL4020-BL4080F	BL4020 - BL4080F

Standard Equipment : BN001GZ : Hook assembly - 141X57-7(1), Hook - 347C14-9(1), Hex. wrench 4 - 783202-0(1), Plastic case - 821943-1(1)

BN001GD201 : Hook assembly - 141X57-7(1), Hook - 347C14-9(1), Hex. wrench 4 - 783202-0(1), Plastic case - 821943-1(1), Battery BL4025 - 191B41-0(2), DC40RA FAST CHARGER DC40RA(1)

BN002GZ : Hook assembly - 141X57-7(1), Hook - 347C14-9(1), Hex. wrench 4 - 783202-0(1), Plastic case - 821943-1(1)

BN002GD201 : Hook assembly - 141X57-7(1), Hook - 347C14-9(1), Hex. wrench 4 - 783202-0(1), Plastic case - 821943-1(1), Battery BL4025 - 191B41-0(2), DC40RA FAST CHARGER DC40RA(1)

The net weight value includes the lightest and heaviest combination of the attachment(s) and battery cartridge(s) which are specified in the instruction manual.
Items of standard equipment and specifications may vary by country or area.



Makita Power Tools India Pvt. Ltd.
Unit II, Sy. Nos. 93/3 & 93/4, Koralur Village, Kasaba Hobli,
Hoskote Taluk, Bengaluru - 560067
Email: info@makita.in | Website: www.makita.in