



Cordless Driver Drill
Cordless Hammer Driver Drill

Satisfy Professional's Needs



XGT
40V^{Li-ion}
max



Enhanced efficiency in heavy-duty tasks with three-speed modes

Work efficiency increased by
about **2 times***
(Medium speed mode)



Cordless Driver Drill
DF003G
13 mm (1/2")



Cordless Hammer Driver Drill
HP003G
13 mm (1/2")

*SPAX screw driving (ø8 x 400 mm) into Douglas Fir
Compared to our previous model



XGT
40V^{Li-ion}
max

Medium speed mode for improved efficiency in heavy-duty tasks

Max. torque **180** N·m



SPAX screw driving (ø8 x 400 mm) into Douglas Fir
With BL4040F battery

HP/DF003G **210**
* Medium speed mode

Our previous model **100**
* Low speed mode

Slow Drilling speed Fast

High-speed rotation at 2,400 min⁻¹

Three-speed modes: Adjustable according to the task and material



Smooth switching with a distinct click

Rotation speed (min ⁻¹)	
Low	0 - 650
Medium	0 - 1,800
High	0 - 2,400

4-LED job light

Positioned below the grip for wide coverage



High brightness / Wide area

About 1-hour runtime in light mode

41 electronic clutch settings in low mode

For precise fastening in a variety of applications



Easy jog dial adjustment

with digital display

Charging Time

	Fast Charging	DC40RA	DC40RC
BL4020 2.0Ah	22 min	30 min	
BL4025 2.5Ah	28 min	38 min	
BL4040 4.0Ah	45 min	67 min	
*BL4040F 4.0Ah	45 min	67 min	
*BL4050F 5.0Ah	50 min	85 min	
BL4080F/H 8.0Ah	76 min	170 min	

*1 Recommended battery

XPT

High water-resistance



Soft start
(in Low-speed mode)

Reduces kickback when starting with high-inertia bits

AFT

Active Feedback sensing Technology

turns the motor off if bit rotation is suddenly forced to stop.



Automatically stops

Cordless Driver Drill	DF003G	
Cordless Hammer Driver Drill	HP003G	
Variable Speed	No load speed	DF003G High: 0 - 2,400 min ⁻¹ / Med.: 0 - 1,800 min ⁻¹ / Low: 0 - 650 min ⁻¹ HP003G High: 0 - 2,400 min ⁻¹ / Med.: 0 - 1,800 min ⁻¹ / Low: 0 - 650 min ⁻¹
Brake	Impacts per minute	DF003G - HP003G High: 0 - 36,000 min ⁻¹ / Med.: 0 - 27,000 min ⁻¹ / Low: 0 - 9,750 min ⁻¹
Reversing	Capacity	DF003G Wood (Self-feed bit): 92 mm (3-5/8") Wood (Hole saw): 152 mm (6") Steel: 20 mm (13/16") HP003G Wood (Self-feed bit): 92 mm (3-5/8") Wood (Hole saw): 152 mm (6") Steel: 20 mm (13/16")
Mechanical 3-Speed	Max fastening torque	DF003G Max: 180 N·m (1,590 in.lbs.) Hard: 150 N·m (1,330 in.lbs.) Soft, High / Med. / Low: 28 / 36 / 88 N·m (250 / 320 / 780 in.lbs.) HP003G Max: 180 N·m (1,590 in.lbs.) Hard: 150 N·m (1,330 in.lbs.) Soft, High / Med. / Low: 28 / 36 / 88 N·m (250 / 320 / 780 in.lbs.)
Keyless Chuck	Clutch torque setting	DF003G High / Med. / Low: 25 / 30 / 41 Chuck capacity 13 mm (1/2") Vibration level* Drilling into metal: 2.5 m/s ² or less
Clutch-equipped	Clutch torque setting	DF003G High / Med. / Low: 25 / 30 / 41 Chuck capacity 13 mm (1/2") Vibration level* Drilling into metal: 2.5 m/s ² or less
Soft Start	Clutch capacity	DF003G High / Med. / Low: 25 / 30 / 41 Chuck capacity 13 mm (1/2") Vibration level* Drilling into metal: 2.5 m/s ² or less
Built-in Job Light	Vibration level*	DF003G High / Med. / Low: 25 / 30 / 41 Chuck capacity 13 mm (1/2") Vibration level* Drilling into metal: 2.5 m/s ² or less
Carrying Case	Uncertainty (K) for Vibration*	DF003G 1.5 m/s ² Sound pressure level* 81 dB(A) Sound power level* 89 dB(A) Noise K factor* 3 dB(A) Dimensions (L x W x H) 196 x 86 x 284 mm (7-3/4 x 3-3/8 x 11-1/8") (Battery) BL4040F Net weight 2.8 - 4.0 kg (6.2 - 8.8 lbs.) (Battery) BL4020-BL4080F
	Sound pressure level*	DF003G 1.5 m/s ² Sound pressure level* 81 dB(A) Sound power level* 89 dB(A) Noise K factor* 3 dB(A) Dimensions (L x W x H) 196 x 86 x 284 mm (7-3/4 x 3-3/8 x 11-1/8") (Battery) BL4040F Net weight 2.8 - 4.0 kg (6.2 - 8.8 lbs.) (Battery) BL4020-BL4080F
	Sound power level*	DF003G 1.5 m/s ² Sound pressure level* 81 dB(A) Sound power level* 89 dB(A) Noise K factor* 3 dB(A) Dimensions (L x W x H) 196 x 86 x 284 mm (7-3/4 x 3-3/8 x 11-1/8") (Battery) BL4040F Net weight 2.8 - 4.0 kg (6.2 - 8.8 lbs.) (Battery) BL4020-BL4080F
	Noise K factor*	DF003G 1.5 m/s ² Sound pressure level* 81 dB(A) Sound power level* 89 dB(A) Noise K factor* 3 dB(A) Dimensions (L x W x H) 196 x 86 x 284 mm (7-3/4 x 3-3/8 x 11-1/8") (Battery) BL4040F Net weight 2.8 - 4.0 kg (6.2 - 8.8 lbs.) (Battery) BL4020-BL4080F
	Dimensions (L x W x H)	DF003G 1.5 m/s ² Sound pressure level* 81 dB(A) Sound power level* 89 dB(A) Noise K factor* 3 dB(A) Dimensions (L x W x H) 196 x 86 x 284 mm (7-3/4 x 3-3/8 x 11-1/8") (Battery) BL4040F Net weight 2.8 - 4.0 kg (6.2 - 8.8 lbs.) (Battery) BL4020-BL4080F
	(Battery)	DF003G 1.5 m/s ² Sound pressure level* 81 dB(A) Sound power level* 89 dB(A) Noise K factor* 3 dB(A) Dimensions (L x W x H) 196 x 86 x 284 mm (7-3/4 x 3-3/8 x 11-1/8") (Battery) BL4040F Net weight 2.8 - 4.0 kg (6.2 - 8.8 lbs.) (Battery) BL4020-BL4080F
	Net weight	DF003G 1.5 m/s ² Sound pressure level* 81 dB(A) Sound power level* 89 dB(A) Noise K factor* 3 dB(A) Dimensions (L x W x H) 196 x 86 x 284 mm (7-3/4 x 3-3/8 x 11-1/8") (Battery) BL4040F Net weight 2.8 - 4.0 kg (6.2 - 8.8 lbs.) (Battery) BL4020-BL4080F
	(Battery)	DF003G 1.5 m/s ² Sound pressure level* 81 dB(A) Sound power level* 89 dB(A) Noise K factor* 3 dB(A) Dimensions (L x W x H) 196 x 86 x 284 mm (7-3/4 x 3-3/8 x 11-1/8") (Battery) BL4040F Net weight 2.8 - 4.0 kg (6.2 - 8.8 lbs.) (Battery) BL4020-BL4080F
	Standard Equipment:	DF003G : Hook - 346317-0(1), Phillips slotted bit - 2-45 784637-8(2) DF003GU201 : BATTERY BL4040F - 1918A1-5(2), Hook - 346317-0(1), Phillips slotted bit - 2-45 784637-8(2), Connector plastic case (type 3) - 821551-8(1), Inner tray 836548-4(1), DC40RA FAST CHARGER DC40RA(1) HP003G : Stopper pole assembly - 122576-8(1), Hook 346317-0(1), Phillips slotted bit - 2-45 784637-8(2) HP003GU201 : Stopper pole assembly - 122576-8(1), BATTERY BL4040F - 1918A1-5(2), Hook 346317-0(1), Phillips slotted bit - 2-45 784637-8(2), Connector plastic case (type 3) 821551-8(1), Inner tray-836548-4(1), DC40RA FAST CHARGER DC40RA(1)

The net weight value includes the lightest and heaviest combination of the attachment(s) for normal and safe use and battery cartridge(s) which are specified in the instruction manual.
Items of standard equipment and specifications may vary by country or area.



Makita Power Tools India Pvt. Ltd.
Unit II, Sy. Nos. 93/3 & 93/4, Koralar Village, Kasaba Hobli,
Hoskote Taluk, Bengaluru - 560067
Email: info@makita.in | Website: www.makita.in